CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

TYAN Thunder K8QSD Pro (S4882-D), AMD Opteron (TM) 854

SPECfp_rate2000 = 98.3

SPECfp_rate_base2000 = 90.5

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Aug-2005 | Hardware Avail: Aug-2005 | Software Avail: Aug-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	56.6	131	4	54.3	137
171.swim	4	127	113	4	124	116
172.mgrid	4	102	82.0	4	93.8	89.1
173.applu	4	102	95.7	4	90.2	108
177.mesa	4	65.3	99.5	4	61.0	106
178.galgel	4	90.0	149	4	81.6	165
179.art	4	111	109	4	77.7	155
183.equake	4	86.1	70.0	4	77.5	77.9
187.facerec	4	84.7	104	4	77.6	114
188.ammp	4	142	71.8	4	132	77.2
189.lucas	4	94.5	98.2	4	94.5	98.2
191.fma3d	4	127	76.8	4	126	77.1
200.sixtrack	4	123	41.5	4	117	43.7
301.apsi	4	152	79.5	4	145	83.1

Hardware

CPU:	AMD Opteron (TM) 854
CPU MHz:	2800
FPU:	Integrated
CPU(s) enabled:	4 cores, 4 chips, 1 core/chip
CPU(s) orderable:	1-4
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB (I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	16x512 MB, DDR400 ECC Reg CL2.5
Disk Subsystem:	SATA, Western Digital WD740GD, 74GB 10000 rpm
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 9 SP2 for AMD64
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.1
File System:	Linux/ext3
System State:	Multi-user, run level 3

Notes/Tuning Information

```
Tested by AMD

 +FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata
 +ACML  means -L/opt/acml2.5.1/pathscale64/lib -lacml,
        which causes linking with AMD Core Math Library V2.5.1

 Baseline optimization
   C programs:       -Ofast -WOPT:mem_opnds=on +FDO
   Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
 Portability Flags:
   178.galgel:  -fixedform

Peak Tuning:
 168.wupwise:    -Ofast -LNO:prefetch_ahead=5:prefetch=3
                 -OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3
                 -IPA:linear=on:plimit=50000:callee_limit=5000
                 -INLINE:aggressive=on
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
171.swim:       -Ofast -LNO:fusion=2 -m3dnow
172.mgrid:      -O3 -LNO:fusion=2:blocking=off
                -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3
                -CG:gcm=off:cflow=off -m3dnow
173.applu:      -Ofast -CG:local_fwd_sched=on
                -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
                -OPT:ro=3 -TENV:X=3
177.mesa:       -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel:     -Ofast -OPT:fast_complex=on +ACML
179.art:        -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32
183.equake:     -Ofast -CG:load_exe=2 -OPT:treeheight=on -WOPT:mem_opnds=on
                -m32 +FDO
187.facerec:    -Ofast -OPT:IEEE_NaN_Inf=off:ro=3 -LNO:fusion=2
                -IPA:plimit=1500 +FDO
188.ammp:       -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
                -fno-math-errno -TENV:X=4 +FDO
189.lucas:       basepeak = true
191.fma3d:      -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
                -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack:=  -O3 -OPT:Ofast:Olimit=6000 -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:       -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
The system under test can be built using a 13" x 16" SSI MEB case and an
Enermax EPS 12 Volt ATX-6ES 660 Watt power supply.
All memory slots were populated with Kingston KRX3200AK2 on all CPU(s).
Taskset utility used to bind CPU(s) to processes.
Memory timings were manually set in BIOS: CL=2.5, TRCD=3, TRAS=6, TRP=3
BIOS Rev E.1.02
```