



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
**ProLiant DL380 G4 (3.8GHz, Intel Xeon)**

**SPECint2000 = 1802**  
**SPECint\_base2000 = 1797**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	110	1269	111	1262	
175.vpr	1400	114	1223	111	1256	
176.gcc	1100	51.9	2118	51.9	2118	
181.mcf	1800	89.1	2019	89.3	2016	
186.crafty	1000	71.1	1407	71.1	1406	
197.parser	1800	117	1535	117	1538	
252.eon	1300	55.7	2335	55.3	2353	
253.perlbnk	1800	81.8	2201	82.1	2193	
254.gap	1100	55.5	1983	55.2	1994	
255.vortex	1900	61.7	3078	61.8	3074	
256.bzip2	1500	112	1336	112	1341	
300.twolf	3000	158	1894	158	1894	

### Hardware

CPU: Intel Xeon (3.8GHz, 2MB L2, 800MHz bus)  
CPU MHz: 3800  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12K micro-ops I + 16KBD on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x2048MB PC2-3200 Dual Rank  
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise SP1  
Compiler: Intel C++ Compiler for 32-bit applications, (Version 8.1 Build 20050524Z)  
Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
MicroQuill Smartheap Library 7.0  
File System: NTFS  
System State: Default

## Notes/Tuning Information

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -Qcxx\_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=\_alloca /F10000000

186.crafty: -DNT\_i386

253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT

254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak = 1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -fast +FDO

253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL380 G4 (3.8GHz, Intel Xeon)

SPECint2000 =	1802
SPECint_base2000 =	1797

SPEC license #:	3	Tested by:	Hewlett-Packard Company	Test date:	Aug-2005	Hardware Avail:	Sep-2005	Software Avail:	May-2005
-----------------	---	------------	-------------------------	------------	----------	-----------------	----------	-----------------	----------

## Notes/Tuning Information (Continued)

```
256.bzip2: -fast -Oa -Qunroll11 +FDO ONESTEP=yes shlw32M.lib
300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Hyper-Threading Technology disabled
```