CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL585 (AMD Opteron (TM) 854)

SPECint_rate2000 = 44.3

SPECint_rate_base2000 = 42.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: May-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	91.6	35.5	2	91.6	35.5
175.vpr	2	95.0	34.2	2	92.0	35.3
176.gcc	2	54.6	46.7	2	54.1	47.2
181.mcf	2	154	27.2	2	128	32.7
186.crafty	2	54.6	42.5	2	49.7	46.7
197.parser	2	104	40.1	2	104	40.1
252.eon	2	46.5	64.8	2	42.8	70.5
253.perlbmk	2	97.1	43.0	2	97.1	43.0
254.gap	2	56.5	45.1	2	56.5	45.1
255.vortex	2	67.7	65.2	2	67.8	65.0
256.bzip2	2	103	33.7	2	102	34.2
300.twolf	2	162	43.0	2	134	52.1

Hardware

CPU:	AMD Opteron (TM) 854
CPU MHz:	2800
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	2,4
Parallel:	No
Primary Cache:	64KBI + 64KBD (on chip) per core
Secondary Cache:	1024KB(I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x2048MB PC3200 CL3.0
Disk Subsystem:	1x36.4GB 15K Ultra320 SCSI
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise SP1
Compiler:	Intel C++ Compiler 8.0 Build 20031211Z Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:       basepeak=yes
  175.vpr:       -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
                  -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
  176.gcc:    -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
  181.mcf:       -fast -QaxN +FDO ONESTEP=yes
  186.crafty:     -fast -arch:SSE2 + FDO ONESTEP=yes
  197.parser:     -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
  252.eon:      -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
                  -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
  253.perlbmk:    basepeak=yes
  254.gap:      basepeak=yes
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    255.vortex:     -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
                   -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
    256.bzip2:      -fast -Qunroll2
    300.twolf:      -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
  BIOS Configuration Notes
    Node Interleaving Disabled
  Other Configuration Notes
    The start /b /wait /affinity command is used to bind CPU(s) to processes.
```