CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X2100

SPECfp_rate2000 = 34.7

SPECfp_rate_base2000 = 31.6

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Sep-2005 | Hardware Avail: Nov-2005 | Software Avail: Nov-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	79.1	46.9	2	76.9	48.3
171.swim	2	119	60.4	2	106	67.9
172.mgrid	2	198	21.1	2	192	21.7
173.applu	2	122	40.0	2	114	42.6
177.mesa	2	109	29.7	2	91.2	35.6
178.galgel	2	150	45.0	2	101	66.4
179.art	2	194	31.0	2	194	31.0
183.equake	2	124	24.3	2	116	26.1
187.facerec	2	103	43.0	2	78.4	56.2
188.ammp	2	190	26.9	2	188	27.1
189.lucas	2	225	20.6	2	225	20.6
191.fma3d	2	174	28.1	2	169	28.8
200.sixtrack	2	161	15.9	2	158	16.2
301.apsi	2	153	39.5	2	140	42.9

Hardware

CPU:	AMD Opteron (TM) 175
CPU MHz:	2200
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	64KBI + 64KBD (on chip) per core
Secondary Cache:	1024KB (I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4GB (4x1GB, PC3200 CL3 DDR Unbufferred SDRAM)
Disk Subsystem:	SATA, 80GB, 10K RPM
Other Hardware:	None

Software

Operating System:	Solaris 10 3/05 HW1
Compiler:	Sun Studio 11
File System:	ufs
System State:	Multi-user

Notes/Tuning Information

```
Compiler invocation:
  C: cc
  F90: f90
  F77: f90

FDO:  PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback
      fdo_pre0:  rm -rf ./feedback.profile


Floating point base flags:
  F90:   -fast -xipo=2 -xarch=amd64 -xprefetch_level=3 ONESTEP=yes
    C:   -fast -xcrossfile -xalias_level=std -xpagesize=2m ONESTEP=yes

Floating point peak flags:
 ONESTEP=yes for all benchmarks

 168.wupwise:   -fast -xpad=common:3969 -xipo=2 -xarch=amd64 -xprefetch_level=3  -xpagesize_heap=2m
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
171.swim:      -fast -xpad=common:3969 -xipo=2 -xvector=simd -xprefetch_level=3 -Qoption iropt
                 -Atile:skewp,-Ainline:cs=700 -xarch=amd64 -Qoption ube_ipa -inl_alt
                 -xpagesize_stack=2m
172.mgrid:     -fast -stackvar -xpad=common:900 -xipo=2 -xarch=amd64 -xprefetch_level=3 -xvector
                 -xpagesize=2m -Qoption ld -M,/usr/lib/ld/map.bssalign
173.applu:       -fast -stackvar -xO4 -xipo=2 -xprefetch_level=3 -xarch=amd64
                 -qoption iropt -Rloop_dist -xpagesize_heap=2m
177.mesa:      -fast -xO4 -xipo=2 -Wd,-iropt-prof -xarch=amd64 -xalias_level=strong -xpagesize=2m +FDO
178.galgel:    -fast -xipo=2 -xpagesize_heap=2m -xprefetch_level=3 -xvector=simd -xarch=amd64
                 RM_SOURCES=lapak.f90
                 EXTRALIBS=-xlic_lib=sunperf
179.art:         basepeak=yes
183.equake:     -fast -xipo=2 -xprefetch -xalias_level=strong -xpagesize=2m -lmopt -lm +FDO
187.facerec:     -fast -xO4 -xipo=2 -xprefetch_level=3 -xpagesize=2m
                 RM_SOURCES=cfftb.f90 cffti.f90 cfftf.f90
                 EXTRALIBS=-xlic_lib=sunperf
188.ammp:       -fast -xO4 -xipo=2 -xarch=amd64 -xalias_level=std -xpagesize_heap=2m -lmopt -lm
189.lucas:       basepeak=yes
191.fma3d:      -fast -fsimple=1 -xipo=2 -xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m +FDO
200.sixtrack:    -fast -xipo=2 -O -xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m
                 -Qoption ld -M,/usr/lib/ld/map.bssalign +FDO
301.apsi:        -fast -xO4 -xipo=2 -xprefetch_level=3 -xarch=amd64 -xpagesize=2m

Portability:
 178.galgel:  -e -fixed -DSPEC_CPU2000_LP64

Shell Environments:
  Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):
  autoup=900
  tune_t_fsflushr=1


Processes were bound to CPUs using submit=pbind

Default BIOS setting was used
```