CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DVA-4G2 Motherboard

SPECint_rate2000 = 42.0

SPECint_rate_base2000 = 42.0

SPEC license #01176 | Tested by: Supermicro | Test date: Sep-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	170	38.3	4	172	37.8
175.vpr	4	242	26.9	4	238	27.3
176.gcc	4	89.2	57.2	4	89.2	57.2
181.mcf	4	380	22.0	4	380	22.0
186.crafty	4	137	33.8	4	137	33.8
197.parser	4	200	41.7	4	197	42.3
252.eon	4	110	54.8	4	110	54.7
253.perlbmk	4	172	48.7	4	172	48.5
254.gap	4	109	46.7	4	109	46.7
255.vortex	4	127	69.4	4	127	69.4
256.bzip2	4	194	35.8	4	196	35.5
300.twolf	4	264	52.8	4	263	52.9

Hardware

CPU:	Intel Xeon Processor (3.80 GHz, 2MB L2, 800 MHz bus)
CPU MHz:	3800
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology Enabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	12k micro-ops I + 16KBD on chip
Secondary Cache:	2048KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	6 x 2.0GB SMART DDR2 400MHz ECC
Disk Subsystem:	250GB Maxtor YAR51HWO SATA HDD
Other Hardware:	N/A

Software

Operating System:	Windows Server 2003 EE SP1
Compiler:	Intel C++ Compiler 9.0 Build 20050430Z (32-bit) Microsoft Visual Studio .Net 2003(for libraries) SmartHeap Library Version 7.4 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib
shlW32M.lib is the SmartHeap Library
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon:   Approved stdcpp src.alt used
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip:     -fast -Qansi_alias -Oa  +FDO
175.vpr:      -fast -Qansi_alias +FDO
176.gcc:      basepeak=yes
181.mcf:      basepeak=yes
186.crafty:   -fast -Qansi_alias -Oa +FDO
197.parser:   -fast -Qansi_alias  +FDO
252.eon:      -fast +FDO
253.perlbmk:  -fast -Qansi_alias +FDO shlW32M.lib
254.gap:      basepeak=yes
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
255.vortex    basepeak=yes
256.bzip2:   -fast -Oa -Qunroll1 +FDO
300.twolf:    -fast -O3 +FDO shlW32M.lib
New 32-bt Windows tools used, approved in May-2005
Tested system was built with SC811S-420 Chassis.
Product description located as of:
http://www.supermicro.com/products/motherboard/Xeon800/E7320/X6DVA-4G2.cfm
The system bus runs at 800MHz
```