CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
H8DS8 Motherboard

SPECint_rate2000 = 73.0

SPECint_rate_base2000 = 68.7

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Apr-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	108	60.2	4	108	60.2
175.vpr	4	121	53.7	4	111	58.7
176.gcc	4	64.7	78.9	4	63.9	79.9
181.mcf	4	217	38.5	4	211	39.6
186.crafty	4	64.0	72.5	4	58.2	79.7
197.parser	4	130	64.1	4	126	66.2
252.eon	4	58.8	103	4	50.7	119
253.perlbmk	4	114	73.5	4	114	73.5
254.gap	4	69.6	73.3	4	69.6	73.3
255.vortex	4	81.2	109	4	73.0	121
256.bzip2	4	128	54.5	4	123	56.4
300.twolf	4	188	73.9	4	156	89.3

Hardware

CPU:	AMD Opteron (TM) 280
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	no
Primary Cache:	64KBI + 64KBD per core on chip
Secondary Cache:	1024KB (I+D) per core on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x Kingston 2GB, Registered, ECC, DDR400, CL3
Disk Subsystem:	1X Hitachi SATA 400 GB 7200RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition w/ SP1
Compiler:	Intel C++ 8.0 build 20040415Z for IA32 Microsoft Visual Studio .NET 7.0.9466 (libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	default

Notes/Tuning Information

```
shlW32M.lib is the SmartHeap library V7.0 from MicroQuill www.microquill.com
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Portability:
  176.gcc:      -Dalloca=_alloca /F10000000
  186.crafty:   -DNT_i386
  253.perlbmk:  -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap:      -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Baseline C:   -fast -arch:SSE2 -Oi- +FDO
Baseline C++: -fast -arch:SSE2 -GX -GR
Peak Tuning:
164.gzip:     basepeak=yes
175.vpr:      -fast -arch:SSE2 +FDO
              -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
176.gcc:      -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
181.mcf:      -fast -QaxN      +FDO
186.crafty:   -fast -arch:SSE2 +FDO
197.parser:         -arch:SSE2 -Oi- -Qipo +FDO
252.eon:      -fast -arch:SSE2 -Qansi_alias +FDO
             -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
253.perlbmk:  basepeak=yes
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 254.gap:      basepeak=yes
 255.vortex:   -fast -arch:SSE -Oi- +FDO shlW32M.lib
               -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
 256.bzip2:    -fast                          -Qunroll2
 300.twolf:    -fast -arch:SSE2 -Qunroll3 -Qansi_alias +FDO shlW32M.lib
The system under test can be built with an ATX 500W power supply
```