CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL580 G3 (3.0GHz, Dual-Core Intel(R) Xeon(R) processor)

SPECint_rate2000 = 15.7

SPECint_rate_base2000 = 15.6

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	142	11.5	1	143	11.4
175.vpr	1	160	10.1	1	156	10.4
176.gcc	1	67.4	18.9	1	67.4	18.9
181.mcf	1	139	15.1	1	139	15.1
186.crafty	1	91.2	12.7	1	91.4	12.7
197.parser	1	153	13.6	1	152	13.7
252.eon	1	69.6	21.7	1	69.0	21.9
253.perlbmk	1	107	19.5	1	106	19.7
254.gap	1	76.7	16.6	1	75.4	16.9
255.vortex	1	84.7	26.0	1	84.7	26.0
256.bzip2	1	156	11.1	1	156	11.1
300.twolf	1	196	17.7	1	196	17.7

Hardware

CPU:	Dual-Core Intel(R) Xeon(R) processor (3.0GHz, 2x2MB L2, 667MHz bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2,4
Parallel:	No
Primary Cache:	12K micro-ops I + 16KBD (on chip) per core
Secondary Cache:	2048KB(I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x1024MB PC2-3200
Disk Subsystem:	1x72.8GB 15K Ultra320 SCSI
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise SP1
Compiler:	Intel C++ Compiler for 32-bit applications, (Version 9.0 Build 20050912Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Base tuning for C programs:   -fast         +FDO  ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO  ONESTEP=yes
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:     -fast               +FDO  ONESTEP=yes
  175.vpr:      -fast               +FDO  ONESTEP=yes
  176.gcc:      basepeak = 1
  181.mcf:      -fast               +FDO  ONESTEP=yes shlw32M.lib
  186.crafty:   -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  197.parser:   -fast               +FDO  ONESTEP=yes
  252.eon:      -fast               +FDO
  253.perlbmk:  -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  254.gap:      -fast               +FDO  ONESTEP=yes
  255.vortex:   -fast               +FDO  ONESTEP=yes shlw32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
  256.bzip2:    -fast -Oa -Qunroll1 +FDO  ONESTEP=yes shlw32M.lib
  300.twolf:    -fast               +FDO              shlw32M.lib
BIOS Configuration Notes
  Hyper-Threading Technology disabled
Other Configuration Notes
  /NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.
```