CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL580 G3 (3.0GHz, Dual-Core Intel(R) Xeon(R) processor)

SPECfp_rate2000 = 15.5

SPECfp_rate_base2000 = 15.2

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	83.7	22.2	1	83.7	22.2
171.swim	1	183	19.7	1	183	19.7
172.mgrid	1	149	14.0	1	149	14.0
173.applu	1	180	13.5	1	179	13.6
177.mesa	1	112	14.5	1	112	14.5
178.galgel	1	102	33.0	1	102	32.9
179.art	1	98.4	30.7	1	98.4	30.7
183.equake	1	94.9	15.9	1	70.8	21.3
187.facerec	1	167	13.2	1	167	13.2
188.ammp	1	250	10.2	1	250	10.2
189.lucas	1	173	13.4	1	174	13.4
191.fma3d	1	193	12.7	1	193	12.7
200.sixtrack	1	188	6.79	1	188	6.78
301.apsi	1	256	11.8	1	256	11.8

Hardware

CPU:	Dual-Core Intel(R) Xeon(R) processor (3.0GHz, 2x2MB L2, 667MHz bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2,4
Parallel:	No
Primary Cache:	12K micro-ops I + 16KBD (on chip) per core
Secondary Cache:	2048KB(I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x1024MB PC2-3200
Disk Subsystem:	1x72.8GB 15K Ultra320 SCSI
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise SP1
Compiler:	Intel C++ Compiler for 32-bit applications, (Version 9.0 Build 20050912Z) Intel Fortran Compiler for 32-bit applications, (Version 9.0 Build 20050912Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use


Base tuning:    -fast -Qansi_alias +FDO
Portability flags:
  178.galgel: -FI /F32000000
Peak tuning:
  168.wupwise:  -fast -Qansi_alias                  +FDO
  171.swim:     -fast                               +FDO ONESTEP=yes
  172.mgrid:    -fast -Qansi_alias                  +FDO
  173.applu:    -fast -Qscalar_rep- -Qauto          +FDO ONESTEP=yes
  177.mesa:     -fast                               +FDO ONESTEP=yes
  178.galgel:   -fast                               +FDO ONESTEP=yes
  179.art:      basepeak=1
  183.equake:   -fast -Oa -Qrcd                     +FDO ONESTEP=yes shlw32M.lib
  187.facerec:  -fast -Qunroll1 -Qscalar_rep- -fpp  +FDO ONESTEP=yes
  188.ammp:     basepeak=1
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
  189.lucas:    -fast
  191.fma3d:    basepeak=1
  200.sixtrack: -fast                                  +FDO
  301.apsi:             basepeak=1
BIOS Configuration Notes
  Hyper-Threading Technology disabled
Other Configuration Notes
  /NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.
```