CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos G5350 (AMD Opteron (TM) 265)

SPECfp_rate2000 = 54.7

SPECfp_rate_base2000 = 50.9

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Oct-2005 | Hardware Avail: Jul-2005 | Software Avail: Jun-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	86.3	86.0	4	86.8	85.5
171.swim	4	297	48.4	4	279	51.6
172.mgrid	4	188	44.5	4	178	46.8
173.applu	4	226	43.1	4	208	46.9
177.mesa	4	206	31.5	4	105	61.8
178.galgel	4	156	86.1	4	147	91.4
179.art	4	97.5	124	4	97.5	124
183.equake	4	128	47.2	4	127	47.7
187.facerec	4	152	58.2	4	152	58.2
188.ammp	4	262	39.0	4	229	44.5
189.lucas	4	177	52.4	4	169	54.8
191.fma3d	4	215	45.4	4	228	42.8
200.sixtrack	4	202	25.3	4	203	25.1
301.apsi	4	268	45.0	4	279	43.3

Hardware

CPU:	AMD Opteron (TM) 265
CPU MHz:	1800
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip, per core
Secondary Cache:	1024KB (I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8 x 1024MB, DDR400 CL3 ECC
Disk Subsystem:	1 x 36GB 10000RPM U320 SCSI HDD
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler:	Intel C++ 9.0 build 20050430Z for IA32 Intel Fortran 9.0 build 20050722Z for IA32 PGI Fortran compiler 6.0-5 PGI C compiler 6.0-5 ACML Version 2.5.3 (bundled with PGI 6.0-5)
File System:	NTFS
System State:	default

Notes/Tuning Information

```
+FDO:
 icl, ifort  : PASS1=-Qprof_gen  PASS2=-Qprof_use
 pgf90       : PASS1=-Mpfi       PASS2=-Mpfo
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran 90 compiler.
pgcc is the PGI C compiler.
ONESTEP is set to 1 for every compile with the PGI compilers.
Portability:
178.galgel:                 -Mfixed
Baseline: C      :  pgcc    -fastsse -Mipa=fast,inline
Baseline: Fortran:  pgf90   -fastsse -Mipa=fast,inline +FDO
Peak tuning:
168.wupwise:        pgf90   -fastsse -Mipa=fast,inline -Mnovect
171.swim:           ifort   -Qipo  -O3  -QaxN -QxW -Qunroll0 +FDO
172.mgrid:          pgf90   -fastsse -Mipa=fast,inline
173.applu:          ifort   -Qipo  -O3 -QaxN -QxW -auto +FDO
177.mesa:           icl     -Qipo -arch:SSE2 -Qunroll1 -Qansi_alias +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
                    -Qoption,f,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel:         pgf90   -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90
                            -Munix -lacml
179.art:            pgcc     basepeak=yes
183.equake:         icl     -fast -arch:SSE2 -QaxW +FDO
187.facerec:        pgf90   -fastsse -Mipa=fast,inline +FDO
188.ammp:           icl     -Oa   -arch:SSE2  -Zp4 -Qansi_alias
189.lucas:          ifort   -Qipo -QxW -Qunroll1
191.fma3d:          pgf90   -Mipa=fast,inline -fastsse -Mnovect +FDO
200.sixtrack:       pgf90   -fastsse -Mipa=fast,inline
301.apsi:           pgf90   -fastsse -Mipa=fast,inline
```