CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS M440, Intel Pentium 4 630

SPECint2000 = 1493

SPECint_base2000 = 1492

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2005 | Hardware Avail: Jul-2005 | Software Avail: Sep-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	140	1000	140	998
175.vpr	1400	135	1040	133	1053
176.gcc	1100	62.0	1774	62.7	1754
181.mcf	1800	95.4	1887	95.3	1888
186.crafty	1000	90.2	1109	90.2	1109
197.parser	1800	143	1257	143	1259
252.eon	1300	69.1	1880	69.1	1880
253.perlbmk	1800	99.3	1813	99.3	1813
254.gap	1100	66.7	1649	66.2	1663
255.vortex	1900	74.4	2555	74.3	2556
256.bzip2	1500	132	1136	132	1135
300.twolf	3000	195	1536	195	1535



Hardware

CPU:	Intel Pentium 4 processor 630
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 16KBD on chip
Secondary Cache:	2048KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4 GB (4x1 GB DDR2-533, 2rank, CL4-4-4, with ECC)
Disk Subsystem:	Serial ATA 7200 rpm
Other Hardware:	

Software

Operating System:	Windows XP Professional, Service Pack 2
Compiler:	Intel(R) C++ Compiler for 32-bit app., Version 9.0, - Build 20050912Z Package ID: W_CC_C_9.0.024 Microsoft Visual Studio .NET 2003 (for libraries) MicroQuill SmartHeap Library 7.4
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
Portability flags:
 176.gcc:     -Dalloca=_alloca /F10000000
 186.crafty:  -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Feedback optimization:
  +FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:
 for C programs:
 -fast +FDO shlW32M.lib
 for C++ program 252.eon:
 -fast -Qcxx_features +FDO

Peak Tuning Flags:
 164.gzip:     -fast +FDO
 175.vpr:      -fast +FDO
 176.gcc:      -fast +FDO
 181.mcf:      -fast +FDO shlW32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 186.crafty:    -fast +FDO
 197.parser:    -fast +FDO
 252.eon:       -fast -Qcxx_features +FDO
 253.perlbmk:   -fast +FDO shlW32M.lib
 254.gap:       -fast +FDO
 255.vortex     -fast +FDO shlW32M.lib
 256.bzip2:     -fast +FDO
 300.twolf:     -fast +FDO shlW32M.lib

Extra Libraries:
 shlW32M.lib = Microquill SmartHeap Library 7.4
 see www.microquill.com

The system bus runs at 800 MHz

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```