CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX motherboard(3.46 GHz, Intel(R) Pentium(R) processor Extreme Edition 955)

SPECfp_rate2000 = 36.7

SPECfp_rate_base2000 = 36.6

SPEC license #: 13 | Tested by: Intel(R) Corporation | Test date: Oct-2005 | Hardware Avail: Jan-2006 | Software Avail: Apr-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	121	61.1	4	121	61.3
171.swim	4	443	32.4	4	443	32.4
172.mgrid	4	279	29.9	4	279	30.0
173.applu	4	327	29.8	4	317	30.7
177.mesa	4	180	36.1	4	180	36.1
178.galgel	4	222	60.5	4	221	60.9
179.art	4	240	50.3	4	240	50.3
183.equake	4	145	41.7	4	145	41.7
187.facerec	4	186	47.4	4	185	47.7
188.ammp	4	369	27.7	4	368	27.8
189.lucas	4	293	31.6	4	293	31.7
191.fma3d	4	306	31.8	4	306	31.8
200.sixtrack	4	255	20.0	4	263	19.4
301.apsi	4	328	36.8	4	334	36.1

Hardware

CPU:	Intel(R) Pentium(R) processor Extreme Edition 955(3.46 GHz, 1066 MHz bus)
CPU MHz:	3466
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 16KBD per core
Secondary Cache:	2MB(I+D) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	1 GB (2 512MB Micron MT16HTF6464AY-667B3 DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem:	Seagate ST3160023AS 160 GB Serial ATA (7200 RPM, 8MB cache)
Other Hardware:	N/A

Software

Operating System:	Windows XP Professional SP2
Compiler:	Intel(R) C++ Compiler 9.0 for 32-bit Build 20050430Z Microsoft Visual Studio .Net 2003(for libraries) SmartHeap Library Version 7.4 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=  -Qprof_gen  PASS2=-Qprof_use
Base tuning for Fortran programs:  -fast -Qansi_alias +FDO
Base tuning for C programs:        -fast shlW32M.lib +FDO
Portability:
178.galgel:   -FI /F32000000
Peak tuning:
168.wupwise:  -fast -Qansi_alias +FDO
171.swim:     -fast -Qansi_alias +FDO
172.mgrid:    -fast -Qansi_alias +FDO
173.applu:  -fast -Qscalar_rep- -Qauto  +FDO
177.mesa:   basepeak=yes
178.galgel:   -fast -Qansi_alias +FDO
179.art:      basepeak=yes
183.equake:   -QxP -Oa -Qrcd -Qipo shlW32M.lib +FDO
187.facerec:  -fast -Qunroll1 -Qscalar_rep- +FDO
188.ammp:     -fast -Oa +FDO shlW32M.lib
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
191.fma3d:    basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi:     -fast +FDO
The system bus runs at 1066 MHz
```