CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS V830, Opteron (TM) 254, Linux 64-bit

SPECint_rate2000 = 22.7

SPECint_rate_base2000 = 20.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Sep-2005 | Software Avail: Dec-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	82.2	19.7	1	82.1	19.8
175.vpr	1	102	15.9	1	99.0	16.4
176.gcc	1	56.5	22.6	1	56.9	22.4
181.mcf	1	230	9.07	1	144	14.5
186.crafty	1	40.0	29.0	1	38.9	29.8
197.parser	1	139	15.0	1	110	19.0
252.eon	1	44.7	33.8	1	38.6	39.1
253.perlbmk	1	94.0	22.2	1	84.0	24.9
254.gap	1	59.4	21.5	1	58.7	21.7
255.vortex	1	67.2	32.8	1	62.7	35.1
256.bzip2	1	95.5	18.2	1	95.5	18.2
300.twolf	1	195	17.9	1	152	22.8

Hardware

CPU:	AMD Opteron 254
CPU MHz:	2800
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD (on chip)
Secondary Cache:	1024KB(I+D) (on chip)
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4 x 512 MB PC3200 CL3-3-3 DDR SDRAM
Disk Subsystem:	SCSI U320
Other Hardware:	None

Software

Operating System:	SLES 9 with SP3 (AMD64) - kernel 2.6.5-7.244-smp
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.3 (for C and C++)
File System:	Linux/ReiserFS
System State:	Multi-User SuSE Run Level 3

Notes/Tuning Information

```
Portability flags:
 186.crafty:  -DLINUX_i386
 252.eon:     -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap:     -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
              -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex:  -DSPEC_CPU2000_LP64

Feedback Optimization:
 +FDO: PASS1=-fb_create fbdata   PASS2=-fb_opt fbdata

Baseline Optimization Flags:
   C programs:       -Ofast +FDO
   C++ programs:     -Ofast +FDO

Peak Tuning Flags:
 164.gzip:   -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr:    -O3 -ipa -m32 +FDO
 176.gcc:    -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 181.mcf:    -O3 -ipa -IPA:field_reorder=on -m32 +FDO
 186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
 197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
 252.eon:    -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
             -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
             -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
 253.perlbmk:-O2 -ipa -OPT:Ofast:transform_to_memlib=off
             -fno-math-errno -IPA:plimit=10000 +FDO
 254.gap:    -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
 255.vortex: -Ofast -OPT:goto=off +FDO
 256.bzip2:  basepeak = true
 300.twolf:  -O2 -CG:gcm=off:p2align_freq=100000
             -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
             -WOPT:mem_opnds=on -m32 +FDO

BIOS default settings with
Node memory interleave disabled, SRAT enabled
taskset has been used to bind processes to CPUs

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```