CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS V830, Opteron (TM) 280, Linux 64-bit

SPECint_rate2000 = 76.0

SPECint_rate_base2000 = 68.1

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Sep-2005 | Software Avail: Dec-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	96.0	67.7	4	95.8	67.8
175.vpr	4	120	53.9	4	116	56.1
176.gcc	4	67.6	75.5	4	68.7	74.3
181.mcf	4	319	26.2	4	198	42.2
186.crafty	4	46.4	99.9	4	45.3	102
197.parser	4	164	51.1	4	128	65.4
252.eon	4	52.0	116	4	45.0	134
253.perlbmk	4	109	76.5	4	97.6	85.5
254.gap	4	73.5	69.5	4	73.3	69.6
255.vortex	4	77.1	114	4	72.1	122
256.bzip2	4	111	62.5	4	111	62.5
300.twolf	4	226	61.6	4	182	76.3

Hardware

CPU:	AMD Opteron 280
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD (on chip) per core
Secondary Cache:	1024KB(I+D) (on chip) per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8 x 512 MB PC3200 CL3-3-3 DDR SDRAM
Disk Subsystem:	SCSI U320
Other Hardware:	None

Software

Operating System:	SLES 9 with SP3 (AMD64) - kernel 2.6.5-7.244-smp
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.3 (for C and C++)
File System:	Linux/ReiserFS
System State:	Multi-User SuSE Run Level 3

Notes/Tuning Information

```
Portability flags:
 186.crafty:  -DLINUX_i386
 252.eon:     -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap:     -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
              -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex:  -DSPEC_CPU2000_LP64

Feedback Optimization:
 +FDO: PASS1=-fb_create fbdata   PASS2=-fb_opt fbdata

Baseline Optimization Flags:
   C programs:       -Ofast +FDO
   C++ programs:     -Ofast +FDO

Peak Tuning Flags:
 164.gzip:   -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr:    -O3 -ipa -m32 +FDO
 176.gcc:    -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 181.mcf:    -O3 -ipa -IPA:field_reorder=on -m32 +FDO
 186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
 197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
 252.eon:    -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
             -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
             -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
 253.perlbmk:-O2 -ipa -OPT:Ofast:transform_to_memlib=off
             -fno-math-errno -IPA:plimit=10000 +FDO
 254.gap:    -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
 255.vortex: -Ofast -OPT:goto=off +FDO
 256.bzip2:  basepeak = true
 300.twolf:  -O2 -CG:gcm=off:p2align_freq=100000
             -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
             -WOPT:mem_opnds=on -m32 +FDO

BIOS default settings with
Node memory interleave disabled, SRAT enabled
taskset has been used to bind processes to CPUs

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```