CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 510 (1900 MHz, 2 CPU)

SPECint_rate2000 = 39.9

SPECint_rate_base2000 = 39.4

SPEC license #: 11 | Tested by: IBM | Test date: Jan-2006 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	242	26.9	4	238	27.3
175.vpr	4	194	33.4	4	192	33.8
176.gcc	4	120	42.4	4	120	42.5
181.mcf	4	150	55.7	4	173	48.2
186.crafty	4	151	30.7	4	123	37.7
197.parser	4	218	38.3	4	220	37.9
252.eon	4	129	46.8	4	129	46.8
253.perlbmk	4	273	30.6	4	269	31.0
254.gap	4	134	38.2	4	133	38.3
255.vortex	4	138	63.8	4	130	67.6
256.bzip2	4	165	42.3	4	160	43.5
300.twolf	4	367	37.9	4	382	36.4

Hardware

CPU:	POWER5+
CPU MHz:	1900
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip (SMT on)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI+32KBD (on chip)/core
Secondary Cache:	1920KB unified, shared (on chip)/chip
L3 Cache:	36MB unified (off-chip)/DCM, 1 DCM/SUT
Other Cache:	None
Memory:	8x2GB
Disk Subsystem:	2x146GB SCSI, 15K RPM
Other Hardware:	None

Software

Operating System:	AIX 5L V5.3
Compiler:	XL C/C++ Enterprise Edition Version 8.0 for AIX
File System:	AIX/JFS2
System State:	Multi-user

Notes/Tuning Information

```
Portability Flags:
  176.gcc:      -ma -DHOST_WORDS_BIG_ENDIAN
  186.crafty:   -DAIX
  253.perlbmk:  -DSPEC_CPU2000_AIX
  254.gap:      -DSYS_IS_BSD -DSYS_STRING_H
                -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
  300.twolf:    -DHAVE_SIGNED_CHAR

Base Optimization Flags:
  C:    -qpdf1/pdf2
        -O5 -blpdata -D_ILS_MACROS
  C++:  -qpdf1/pdf2
        -O4 -qalign=natural

Peak Optimization Flags
  164.gzip:     -qpdf1/pdf2
                -O4 -qfdpr -blpdata
                fdpr -q -O3
  175.vpr:      -qpdf1/pdf2
                -O5 -qfdpr -blpdata
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
                fdpr -q -O3
  176.gcc:      -qpdf1/pdf2
                -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
  181.mcf:      -qpdf1/pdf2
                -O4 -qalign=natural -blpdata
  186.crafty:   -qpdf1/pdf2
                -O4 -qalign=natural -q64 -lhmu -blpdata
  197.parser:   -qpdf1/pdf2
                -O4 -qfdpr -D_ILS_MACROS -blpdata
                fdpr -q -O3
  252.eon:      -qpdf1/pdf2
                -O4 -qalign=natural
  253.perlbmk:  -qpdf1/pdf2
                -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata -lhmu
  254.gap:      -qpdf1/pdf2
                -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
  255.vortex:   -qpdf1/pdf2
                -O4 -qfdpr -lhmu -blpdata
                fdpr -q -O3
  256.bzip2:    -qpdf1/pdf2
                -O5 -qfdpr -blpdata
                fdpr -q -O3
  300.twolf:    -O5 -qfdpr -blpdata
                fdpr -q -O3


The installed OS level is AIX 5L for POWER version 5.3 with the 5300-04 Recommended Technology Level.

SMT:  Acronym for "Simultaneous Multi-Threading". A processor technology that allows
      the simultaneous execution of multiple thread contexts within a single processor
      core. (Enabled by default)
DCM:  Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)
SUT:  Acronym for "System Under Test"

Extended C:     IBM XL C for AIX invoked as cc
C++:            IBM XL C for AIX invoked as xlC

ulimits set to unlimited.
Large page mode and memory affinity were set as follows:
    vmo -r -o lgpg_regions=512 -o lgpg_size=16777216
    chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
    shutdown -rF
    export MEMORY_AFFINITY=MCM

The following config-file entry was used to assign each benchmark process to a core:
     submit = bindprocessor $$ $SPECUSERNUM; $command
The "bindprocessor" AIX command binds a process to a CPU core.
```