



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 560Q (1500 MHz, 1 CPU)

SPECfp2000 = 2360
SPECfp_base2000 = 2197

SPEC license #: 11 Tested by: IBM Test date: Nov-2005 Hardware Avail: Feb-2006 Software Avail: Feb-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	81.2	1972	70.1	2283
171.swim	3100	105	2962	105	2962
172.mgrid	1800	89.4	2013	84.5	2129
173.applu	2100	127	1656	111	1892
177.mesa	1400	138	1016	132	1061
178.galgel	2900	62.4	4648	43.3	6700
179.art	2600	21.3	12195	20.4	12754
183.quake	1300	28.1	4630	27.6	4712
187.facerec	1900	92.3	2058	90.1	2108
188.amp	2200	198	1110	176	1250
189.lucas	2000	47.9	4177	46.9	4263
191.fma3d	2100	162	1298	157	1339
200.sixtrack	1100	165	668	165	668
301.apsi	2600	183	1422	183	1419

Hardware

CPU: POWER5+
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 1 core, 4 chips, 2 cores/chip (SMT off)
CPU(s) orderable: 8,16
Parallel: No
Primary Cache: 64KBI+32KBD (on chip)/core
Secondary Cache: 1920KB unified, shared (on chip)/chip
L3 Cache: 2x36MB unified (off-chip)/QCM, 1 QCM/SUT
Other Cache: None
Memory: 16x2GB
Disk Subsystem: 2x36GB SCSI, 15K RPM
Other Hardware: None

Software

Operating System: AIX 5L V5.3
Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX
XL Fortran Enterprise Edition Version 10.1 for AIX
Other Software: ESSL 4.2.0.3
File System: AIX/JFS2
System State: Multi-user

Notes/Tuning Information

Portability Flags:

-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,
178.galgel, 200.sixtrack, 301.apsi
-qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

Base Optimization Flags:

Fortran: -O5 -lhmu -blpdata -lmass
C: -qpdf1/pdf2
-O5 -blpdata -qalign=natural

Peak Optimization Flags

168.wupwise: -O5 -qsave -blpdata -lhmu -lmass
171.swim: basepeak=1
172.mgrid: -qpdf1/pdf2
-O4 -qarch=auto -qtune=auto -qipa=partition=large -q64 -blpdata
173.applu: -O5 -qarch=pwr3 -qtune=pwr3 -qalign=struct=natural -qfdpr -q64 -blpdata
fdpr -q -O3



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 560Q (1500 MHz, 1 CPU)

SPECfp2000 = 2360

SPECfp_base2000 = 2197

SPEC license #: 11 | Tested by: IBM | Test date: Nov-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Notes/Tuning Information (Continued)

```

177.mesa:      -qpdf1/pdf2
               -O5 -qfdpr
               fdpr -q -O3
178.galgel:    -qpdf1/pdf2
               -O5 -qfdpr -lhmu -blpdata -lmass -qessl -lessl
               fdpr -q -O3
179.art:       -qpdf1/pdf2
               -O5 -qhot=arraypad -Q -qalign=natural -blpdata -lhmu
183.earthquake: -qpdf1/pdf2
               -O3 -qarch=auto -qtune=auto -qipa=level=2 -blpdata
187.facerec:   -O5 -qsave -blpdata
188.ammp:      -O5 -qalign=natural -qfdpr -blpdata -lhmu
               fdpr -q -O3
189.lucas:     -O3 -qhot -qarch=auto -qtune=auto -qfdpr -blpdata -qessl -lessl
               fdpr -q -O3
191.fma3d:     -qpdf1/pdf2
               -O3 -qarch=auto -qtune=auto -qipa=level=2 -q64 -lhmu -blpdata -lmass
200.sixtrack:  -qpdf1/pdf2
               -O4 -qfdpr
301.apsi:      -O5

```

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-03 Recommended Technology Level.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

QCM: Acronym for "Quad-Core Module" (Two dual-core processor chips + two L3-cache chips)

SUT: Acronym for "System Under Test"

ESSL: Engineering and Scientific Subroutine Library

```

ANSI C89:      IBM XL C for AIX invoked as xlc
Fortran 77:    IBM XL Fortran for AIX invoked as xlf90
Fortran 90:    IBM XL Fortran for AIX invoked as xlf90

```

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=800 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \${$} \${$SPECUSERNUM}; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.

Seven cores were deconfigured and SMT disabled using the AIX commands

```

smtctl -m off -w boot
bosboot -aD
shutdown -rF
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu

```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 560Q (1500 MHz, 1 CPU)

SPECfp2000 = 2360

SPECfp_base2000 = 2197

SPEC license #: 11 | Tested by: IBM | Test date: Nov-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Notes/Tuning Information (Continued)