CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX150 S4, Intel Pentium D 930 processor, 3.0 GHz

SPECfp_rate2000 = 36.8

SPECfp_rate_base2000 = 36.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Mar-2006 | Hardware Avail: May-2006 | Software Avail: Jan-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	62.2	59.7	2	62.2	59.7
171.swim	2	218	33.0	2	218	33.0
172.mgrid	2	139	29.9	2	139	29.9
173.applu	2	170	28.7	2	170	28.7
177.mesa	2	88.7	36.6	2	88.7	36.6
178.galgel	2	95.8	70.2	2	95.8	70.2
179.art	2	52.7	115	2	52.7	115
183.equake	2	81.0	37.2	2	81.0	37.2
187.facerec	2	107	41.3	2	107	41.3
188.ammp	2	178	28.6	2	178	28.6
189.lucas	2	145	32.1	2	145	32.1
191.fma3d	2	161	30.3	2	161	30.3
200.sixtrack	2	184	13.9	2	184	13.9
301.apsi	2	211	28.5	2	211	28.5

Hardware

CPU:	Intel Pentium D 930 processor (3.0 GHz, 2x2MB SLC, 800 MHz system bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 16KBD on chip, per core
Secondary Cache:	2048KB(I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x2048 MB DDRII-RAM PC2-4200E
Disk Subsystem:	Fujitsu MAS3735NC (SCSI, 15 krpm, 73GB)
Other Hardware:	none

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 9 with SP3 Kernel 2.6.5-7.244-smp on an x86_64
Compiler:	Intel C++ and Fortran Compiler 9.0 for EM64T Build 20060120 (for 64-bit applications)
File System:	ext3
System State:	Multi-user run level 3

Notes/Tuning Information

```
GENERAL
+FDO implies feedback-directed optimization
PASS1: -prof_gen  PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
   for Fortran and C programs: -fast +FDO

Peak tuning flags
   same as baseline (basepeak=true set globally)
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries