CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

H8DSL-HTi Motherboard (AMD Opteron (TM) 256)

SPECfp2000 = 2030

SPECfp_base2000 = 1860

SPEC license #01176 | Tested by: Supermicro | Test date: Apr-2006 | Hardware Avail: Apr-2006 | Software Avail: Oct-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	54.8	2918	55.4	2890
171.swim	3100	138	2243	132	2340
172.mgrid	1800	103	1752	103	1754
173.applu	2100	138	1526	127	1652
177.mesa	1400	122	1146	59.8	2342
178.galgel	2900	93.3	3108	87.7	3305
179.art	2600	56.8	4581	56.8	4581
183.equake	1300	75.4	1724	74.8	1739
187.facerec	1900	89.2	2131	89.2	2131
188.ammp	2200	171	1290	140	1570
189.lucas	2000	109	1842	96.5	2073
191.fma3d	2100	125	1685	123	1713
200.sixtrack	1100	122	904	121	906
301.apsi	2600	167	1556	167	1553



Hardware

CPU:	AMD Opteron (TM) 256
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1
Parallel:	no
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB (I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4 X Apacer 78.A1071.404, 2GB DDR-400 CL3 ECC Reg
Disk Subsystem:	1 X IDE, Seagate ST3250823A 250GB
Other Hardware:	None

Software

Operating System:	Windows server 2003 Enterprise Edition 32-bit Version w/ Service Pack 1
Compiler:	Intel C++ 9.0 build 20050912Z for IA32, Intel Fortran 9.0 build 20050912Z for IA32, Microsoft Visual Studio .NET 2003 7.0.9466 (libraries) PGI Fortran compiler 6.0-5 for Windows XP, PGI C compiler 6.0-5 for Windows XP, ACML Version 2.5.3 (bundled with PGI 6.0-5)
File System:	NTFS
System State:	default

Notes/Tuning Information

```
+FDO:
 icl, ifort  : PASS1=-Qprof_gen  PASS2=-Qprof_use
 pgf90       : PASS1=-Mpfi       PASS2=-Mpfo
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran 90 compiler.
pgcc is the PGI C compiler.
ONESTEP is set to 1 for every compile with the PGI compilers.
Portability:
178.galgel:                 -Mfixed
Baseline: C      :  pgcc    -fastsse -Mipa=fast,inline
Baseline: Fortran:  pgf90   -fastsse -Mipa=fast,inline +FDO
Peak tuning:
168.wupwise:        pgf90   -fastsse -Mipa=fast,inline -Mnovect
171.swim:           ifort   -Qipo  -O3  -QaxN -QxW -Qunroll0 +FDO
172.mgrid:          pgf90   -fastsse -Mipa=fast,inline
173.applu:          ifort   -Qipo  -O3 -QaxN -QxW -auto +FDO
177.mesa:           icl     -Qipo -QxW -Qunroll1 -Qansi_alias +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
                        -Qoption,c,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel:         pgf90   -fastsse -Mipa=fast,safe -Munix -lacml
                            RM_SOURCES=lapak.f90
179.art:            pgcc     basepeak=yes
183.equake:         icl     -O3 -Qipo -QxW +FDO
187.facerec:        pgf90   basepeak=1
188.ammp:           icl     -Oa   -QxW  -Zp4 -Qansi_alias
189.lucas:          ifort   -Qipo -QxW -Qunroll1
191.fma3d:          pgf90   -Mipa=fast,inline -fastsse -Mnovect +FDO
200.sixtrack:       pgf90   -fastsse -Mipa=fast,inline
301.apsi:           pgf90   -fastsse -Mipa=fast,inline
Tested systm was built with chassis SC813T-500C,
Product description located as of:
http://www.supermicro.com/Aplus/motherboard/Opteron/HT1000/H8DSL-HTi.cfm
To ensure system stability, a 420W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Other Configuration Notes
The start /b /wait /affinity command is used to bind CPU(s) to processes.
```