CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX150 S4, Intel Pentium D 950 processor, 3.40 GHz

SPECfp_rate2000 = 39.0

SPECfp_rate_base2000 = 39.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Apr-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	58.7	63.2	2	58.7	63.2
171.swim	2	217	33.1	2	217	33.1
172.mgrid	2	137	30.5	2	137	30.5
173.applu	2	165	29.5	2	165	29.5
177.mesa	2	78.5	41.4	2	78.5	41.4
178.galgel	2	91.4	73.6	2	91.4	73.6
179.art	2	49.7	121	2	49.7	121
183.equake	2	80.7	37.4	2	80.7	37.4
187.facerec	2	98.9	44.6	2	98.9	44.6
188.ammp	2	161	31.6	2	161	31.6
189.lucas	2	143	32.6	2	143	32.6
191.fma3d	2	150	32.4	2	150	32.4
200.sixtrack	2	162	15.7	2	162	15.7
301.apsi	2	192	31.5	2	192	31.5

Hardware

CPU:	Intel Pentium D 950 processor (3.40 GHz, 2x2MB L2, 800 MHz system bus)
CPU MHz:	3400
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops I + 16KBD on chip, per core
Secondary Cache:	2048KB(I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x2GB DDRII-RAM PC2-4200E (CAS 4-4-4)
Disk Subsystem:	Fujitsu MAS3735NC (SCSI, 15 krpm, 73GB)
Other Hardware:	none

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 9 with SP3 Kernel 2.6.5-7.244-smp on an x86_64
Compiler:	Intel C++ and Fortran Compiler 9.0 for EM64T Build 20060120 (for 64-bit applications)
File System:	ext3
System State:	Multi-user run level 3

Notes/Tuning Information

```
GENERAL
+FDO implies feedback-directed optimization
PASS1: -prof_gen  PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
   for Fortran and C programs: -fast +FDO

Peak tuning flags
   same as baseline (basepeak=true set globally)
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries