# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon 5160 processor, 3.0 GHz

SPECfp2000 = 2783

SPECfp_base2000 = 2783

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

| Benchmark | Reference Time | Base Runtime | Base Ratio | Runtime | Ratio |
|---|---|---|---|---|---|
| 168.wupwise | 1600 | 43.0 | 3720 | 43.0 | 3720 |
| 171.swim | 3100 | 111 | 2797 | 111 | 2797 |
| 172.mgrid | 1800 | 92.1 | 1954 | 92.1 | 1954 |
| 173.applu | 2100 | 98.0 | 2143 | 98.0 | 2143 |
| 177.mesa | 1400 | 45.2 | 3095 | 45.2 | 3095 |
| 178.galgel | 2900 | 41.0 | 7077 | 41.0 | 7077 |
| 179.art | 2600 | 21.5 | 12089 | 21.5 | 12089 |
| 183.equake | 1300 | 48.9 | 2658 | 48.9 | 2658 |
| 187.facerec | 1900 | 63.4 | 2996 | 63.4 | 2996 |
| 188.ammp | 2200 | 102 | 2150 | 102 | 2150 |
| 189.lucas | 2000 | 95.3 | 2098 | 95.3 | 2098 |
| 191.fma3d | 2100 | 101 | 2071 | 101 | 2071 |
| 200.sixtrack | 1100 | 95.8 | 1149 | 95.8 | 1149 |
| 301.apsi | 2600 | 153 | 1696 | 153 | 1696 |




### Hardware

| | |
|---|---|
| CPU: | Intel Xeon 5160 processor (3.0 GHz, 4MB L2, 1333 MHz system bus) |
| CPU MHz: | 3000 |
| FPU: | Integrated |
| CPU(s) enabled: | 2 cores, 1 chip, 2 cores/chip |
| CPU(s) orderable: | 1,2 |
| Parallel: | No |
| Primary Cache: | 32KBI + 32KBD on chip, per core |
| Secondary Cache: | 4096KB(I+D) on chip, shared |
| L3 Cache: | N/A |
| Other Cache: | N/A |
| Memory: | 8x1GB DDRII-RAM PC2-5300F (CAS 5-5-5) |
| Disk Subsystem: | Seagate ST336754SS (SAS, 15.4krpm, 36GB) |
| Other Hardware: | none |

### Software

| | |
|---|---|
| Operating System: | 64-Bit SUSE LINUX Enterprise Server 9 with SP3 Kernel 2.6.5-7.244-smp on an x86_64 |
| Compiler: | Intel C++ and Fortran Compiler 9.0 for EM64T Build 20060120 (for 64-bit applications) |
| File System: | ext3 |
| System State: | Multi-user run level 3 |

## Notes/Tuning Information

```
GENERAL
+FDO implies feedback-directed optimization
PASS1: -prof_gen  PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
   for Fortran and C programs: -fast +FDO

Peak tuning flags
   same as baseline (basepeak=true set globally)
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries