# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G4 (3.0GHz, Intel Xeon processor 7041)

SPECint_rate2000 = 61.0

SPECint_rate_base2000 = 60.7

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: May-2006




| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|---|---|---|---|---|---|---|
| 164.gzip | 4 | 142 | 45.7 | 4 | 142 | 45.7 |
| 175.vpr | 4 | 161 | 40.2 | 4 | 157 | 41.4 |
| 176.gcc | 4 | 67.2 | 75.9 | 4 | 67.2 | 75.9 |
| 181.mcf | 4 | 202 | 41.4 | 4 | 202 | 41.4 |
| 186.crafty | 4 | 88.6 | 52.3 | 4 | 88.5 | 52.4 |
| 197.parser | 4 | 151 | 55.3 | 4 | 150 | 55.5 |
| 252.eon | 4 | 63.6 | 94.9 | 4 | 63.6 | 94.8 |
| 253.perlbmk | 4 | 105 | 79.4 | 4 | 103 | 80.9 |
| 254.gap | 4 | 87.7 | 58.2 | 4 | 86.9 | 58.7 |
| 255.vortex | 4 | 83.5 | 106 | 4 | 83.6 | 105 |
| 256.bzip2 | 4 | 154 | 45.1 | 4 | 154 | 45.1 |
| 300.twolf | 4 | 195 | 71.4 | 4 | 195 | 71.4 |

### Hardware

| | |
|---|---|
| CPU: | Intel Xeon processor 7041 (3.0GHz, 2x2MB L2, 800MHz bus) |
| CPU MHz: | 3000 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled) |
| CPU(s) orderable: | 1,2,4 |
| Parallel: | No |
| Primary Cache: | 12K micro-ops I + 16KBD (on chip) per core |
| Secondary Cache: | 2048KB(I+D) (on chip) per core |
| L3 Cache: | N/A |
| Other Cache: | N/A |
| Memory: | 8x2048MB PC2-3200 dual-rank |
| Disk Subsystem: | 1x36GB SAS |
| Other Hardware: | |

### Software

| | |
|---|---|
| Operating System: | Windows Server 2003 Enterprise SP1 |
| Compiler: | Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)<br>Microsoft Visual Studio .NET 7.0.9466 (for libraries)<br>MicroQuill Smartheap Library 7.0 |
| File System: | NTFS |
| System State: | Default |

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Base tuning for C programs:   -fast         +FDO  ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO  ONESTEP=yes
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:     -fast               +FDO  ONESTEP=yes
  175.vpr:      -fast               +FDO  ONESTEP=yes
  176.gcc:      basepeak=1
  181.mcf:      -fast               +FDO  ONESTEP=yes shlw32M.lib
  186.crafty:   -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  197.parser:   -fast               +FDO  ONESTEP=yes
  252.eon:      -fast               +FDO
  253.perlbmk:  -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  254.gap:      -fast               +FDO  ONESTEP=yes
  255.vortex:   -fast               +FDO  ONESTEP=yes shlw32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

```
    256.bzip2:    basepeak=1
    300.twolf:    -fast                +FDO              shlw32M.lib
  BIOS Configuration Notes
    Hyper-Threading Technology disabled
```