CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R720 (3.2 GHz Intel Xeon Processor 5060)

SPECfp_rate2000 = 60.0

SPECfp_rate_base2000 = 60.0

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2006 | Hardware Avail: Jun-2006 | Software Avail: Dec-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	81.4	91.2	4	81.4	91.2
171.swim	4	293	49.1	4	293	49.1
172.mgrid	4	189	44.3	4	189	44.3
173.applu	4	209	46.5	4	209	46.5
177.mesa	4	84.6	76.7	4	84.6	76.7
178.galgel	4	106	127	4	106	127
179.art	4	72.2	167	4	72.2	167
183.equake	4	136	44.5	4	136	44.5
187.facerec	4	136	64.7	4	136	64.7
188.ammp	4	189	53.9	4	189	53.9
189.lucas	4	200	46.3	4	200	46.3
191.fma3d	4	201	48.5	4	201	48.5
200.sixtrack	4	172	29.6	4	172	29.6
301.apsi	4	236	51.0	4	236	51.0

Hardware

CPU:	Intel Xeon Processor 5060 (3.2 GHz, 2x2MB L2, 1066MHz system bus)
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip(Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	12KB(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache:	2048KB(I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8 x 2048MB ECC FB-DIMM DDR2-667
Disk Subsystem:	1 x 73GB 10000RPM SAS HDD
Other Hardware:	

Software

Operating System:	Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T (Kernel 2.6.9-34.ELsmp)
Compiler:	Intel C++ Compiler 9.0 Build 20051201 for EM64T Intel Fortran Compiler 9.0 Build 20051201 for EM64T
File System:	ext3
System State:	Runlevel 3

Notes/Tuning Information

```
GENERAL
 ONESTEP=yes for all benchmarks
 +FDO :  PASS1= -prof_gen   PASS2= -prof_use
PORTABILITY FLAGS
 -DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran
BASE TUNING
 Baseline optimizations for C and Fortran: -fast +FDO
PEAK TUNING
 basepeak=yes set for all benchmarks
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
```