# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5140 processor, 2.33 GHz

SPECint_rate2000 = 50.5

SPECint_rate_base2000 = 50.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006




| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|---|---|---|---|---|---|---|
| 164.gzip | 2 | 98.5 | 33.0 | 2 | 98.5 | 33.0 |
| 175.vpr | 2 | 89.3 | 36.4 | 2 | 89.3 | 36.4 |
| 176.gcc | 2 | 47.3 | 54.0 | 2 | 47.3 | 54.0 |
| 181.mcf | 2 | 88.9 | 47.0 | 2 | 88.9 | 47.0 |
| 186.crafty | 2 | 46.9 | 49.4 | 2 | 46.9 | 49.4 |
| 197.parser | 2 | 101 | 41.3 | 2 | 101 | 41.3 |
| 252.eon | 2 | 43.1 | 70.0 | 2 | 43.1 | 70.0 |
| 253.perlbmk | 2 | 65.9 | 63.4 | 2 | 65.9 | 63.4 |
| 254.gap | 2 | 48.9 | 52.1 | 2 | 48.9 | 52.1 |
| 255.vortex | 2 | 52.3 | 84.4 | 2 | 52.3 | 84.4 |
| 256.bzip2 | 2 | 95.4 | 36.5 | 2 | 95.4 | 36.5 |
| 300.twolf | 2 | 113 | 61.7 | 2 | 113 | 61.7 |

### Hardware

| | |
|---|---|
| CPU: | Intel Xeon 5140 processor (2.33 GHz, 4MB L2, 1333 MHz system bus) |
| CPU MHz: | 2333 |
| FPU: | Integrated |
| CPU(s) enabled: | 2 cores, 1 chip, 2 cores/chip |
| CPU(s) orderable: | 1,2 |
| Parallel: | No |
| Primary Cache: | 32KBI + 32KBD on chip, per core |
| Secondary Cache: | 4096KB(I+D) on chip, shared |
| L3 Cache: | N/A |
| Other Cache: | N/A |
| Memory: | 8x1GB DDRII-RAM PC2-5300F (CAS 5-5-5) |
| Disk Subsystem: | Seagate ST373454SS (SAS, 15.4krpm, 73GB) |
| Other Hardware: | none |

### Software

| | |
|---|---|
| Operating System: | Windows Server 2003 Enterprise Edition + SP1 (32-bit) |
| Compiler: | Intel C++ Compiler 9.1 Build 20060323Z (for 32-bit applications), Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries), SmartHeap Library Version 8.0 from http://www.microquill.com |
| File System: | NTFS |
| System State: | Default |

## Notes/Tuning Information

```
GENERAL
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafy:   -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags
   for C programs:   -fast +FDO shlW32M.lib
   for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib

Peak tuning flags
   same as baseline (basepeak=true set globally)

The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of
the operating system.
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries