CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML350 G5 (3.00GHz, Intel Xeon processor 5160)

SPECfp_rate2000 = 76.8

SPECfp_rate_base2000 = 72.2

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	71.5	104	4	71.5	104
171.swim	4	339	42.4	4	340	42.3
172.mgrid	4	220	38.0	4	220	37.9
173.applu	4	250	39.0	4	167	58.5
177.mesa	4	48.3	135	4	43.5	149
178.galgel	4	62.5	215	4	62.5	215
179.art	4	55.2	219	4	55.2	219
183.equake	4	134	44.9	4	107	56.3
187.facerec	4	94.1	93.7	4	84.5	104
188.ammp	4	123	83.2	4	123	83.2
189.lucas	4	220	42.2	4	219	42.4
191.fma3d	4	183	53.2	4	183	53.2
200.sixtrack	4	97.5	52.4	4	97.5	52.4
301.apsi	4	197	61.3	4	193	62.7

Hardware

CPU:	Intel Xeon processor 5160 (3.00GHz, 4MB L2 shared, 1333MHz bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Parallel:	No
Primary Cache:	32KBI + 32KBD (on chip) per core
Secondary Cache:	4096KB(I+D) (on chip) shared
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x2048MB PC2-5300F
Disk Subsystem:	1x36GB 15K SAS
Other Hardware:	

Software

Operating System:	RedHat Enterprise Linux 4.0 Advanced Server Update 3 Kernel 2.6.9-34.ELsmp
Compiler:	Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323) Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323) PathScale EKOPath(TM) Compiler Suite, Release 2.4
File System:	ext2
System State:	multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -prof_gen  PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs:  icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs:  ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel:   -FI
Peak tuning:
168.wupwise:  basepeak=1
171.swim:     pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid:    pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
              -OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu:    pathf95 -O3 -ipa -CG:load_exe=0
              -LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
              -OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
177.mesa:     pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel:   basepeak=1
179.art:      basepeak=1
183.equake:   icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec:  pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
              -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t
188.ammp:     basepeak=1
189.lucas:    ifort -fast ONESTEP=yes
191.fma3d:    basepeak=1
200.sixtrack: basepeak=1
301.apsi:     pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
  BIOS Configuration Notes
    Power Regulator set to Static High Performance Mode
```