CFP2000 Result

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5110 processor, 1.60 GHz

SPECfp_rate2000 = 31.5

SPECfp_rate_base2000 = 31.5

SPEC license #: 22	Tested by: Fujitsu Siemens Computers	Test date: Jul-2006	Hardware Avail: Jul-2006	Software Avail: Jan-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	78.7	47.2	2	78.7	47.2
171.swim	2	263	27.3	2	263	27.3
172.mgrid	2	184	22.6	2	184	22.6
173.applu	2	198	24.6	2	198	24.6
177.mesa	2	84.4	38.5	2	84.4	38.5
178.galgel	2	92.9	72.4	2	92.9	72.4
179.art	2	68.9	87.5	2	68.9	87.5
183.equake	2	109	27.8	2	109	27.8
187.facerec	2	119	37.1	2	119	37.1
188.ammp	2	198	25.7	2	198	25.7
189.lucas	2	186	24.9	2	186	24.9
191.fma3d	2	198	24.7	2	198	24.7
200.sixtrack	2	182	14.0	2	182	14.0
301.apsi	2	257	23.5	2	257	23.5

Hardware

CPU:	Intel Xeon 5110 processor (1.60 GHz, 4MB SLC, 1066 MHz system bus)
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4096KB(I+D) on chip, per chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x1024 MB DDRII-RAM PC2-4200F (CAS 4-4-4)
Disk Subsystem:	Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware:	none

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 9 with SP3 Kernel 2.6.5-7.244-smp on an x86_64
Compiler:	Intel C++ and Fortran Compiler 9.0 for EM64T Build 20060120 (for 64-bit applications)
File System:	ext2
System State:	Multi-user run level 3

Notes/Tuning Information

```
GENERAL
+FDO implies feedback-directed optimization
PASS1: -prof_gen  PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
   for Fortran and C programs: -fast +FDO

Peak tuning flags
   same as baseline (basepeak=true set globally)
```

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5110 processor, 1.60 GHz

SPECfp_rate2000 = 31.5
SPECfp_rate_base2000 = 31.5

SPEC license #: 22	Tested by: Fujitsu Siemens Computers	Test date: Jul-2006	Hardware Avail: Jul-2006	Software Avail: Jan-2006

Notes/Tuning Information (Continued)

```
The system bus runs at 1066 MHz

This result was measured with 64-bit binaries using the 64-bit version of
the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```