CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5140 processor, 2.33 GHz

SPECfp_rate2000 = 41.8

SPECfp_rate_base2000 = 41.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	60.5	61.4	2	60.5	61.4
171.swim	2	211	34.1	2	211	34.1
172.mgrid	2	142	29.3	2	142	29.3
173.applu	2	155	31.4	2	155	31.4
177.mesa	2	59.2	54.9	2	59.2	54.9
178.galgel	2	66.6	101	2	66.6	101
179.art	2	52.0	116	2	52.0	116
183.equake	2	87.9	34.3	2	87.9	34.3
187.facerec	2	88.7	49.7	2	88.7	49.7
188.ammp	2	141	36.3	2	141	36.3
189.lucas	2	149	31.1	2	149	31.1
191.fma3d	2	149	32.7	2	149	32.7
200.sixtrack	2	125	20.4	2	125	20.4
301.apsi	2	194	31.1	2	194	31.1

Hardware

CPU:	Intel Xeon 5140 processor (2.33 GHz, 4MB SLC, 1333 MHz system bus)
CPU MHz:	2333
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4096KB(I+D) on chip, per chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x1024 MB DDRII-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem:	Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware:	none

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 9 with SP3 Kernel 2.6.5-7.244-smp on an x86_64
Compiler:	Intel C++ and Fortran Compiler 9.0 for EM64T Build 20060120 (for 64-bit applications)
File System:	ext2
System State:	Multi-user run level 3

Notes/Tuning Information

```
GENERAL
+FDO implies feedback-directed optimization
PASS1: -prof_gen  PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
   for Fortran and C programs: -fast +FDO

Peak tuning flags
   same as baseline (basepeak=true set globally)
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries