CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2210

SPECfp_rate2000 = 31.6

SPECfp_rate_base2000 = 29.0

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Oct-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	80.5	46.1	2	80.8	46.0
171.swim	2	205	35.1	2	187	38.4
172.mgrid	2	157	26.6	2	157	26.6
173.applu	2	190	25.7	2	180	27.1
177.mesa	2	198	16.4	2	97.7	33.2
178.galgel	2	139	48.3	2	130	51.6
179.art	2	81.7	73.8	2	81.7	73.8
183.equake	2	107	28.3	2	104	29.0
187.facerec	2	134	33.0	2	134	33.0
188.ammp	2	254	20.1	2	220	23.2
189.lucas	2	144	32.1	2	131	35.4
191.fma3d	2	194	25.2	2	189	25.7
200.sixtrack	2	201	12.7	2	201	12.7
301.apsi	2	257	23.5	2	257	23.5

Hardware

CPU:	AMD Opteron (TM) 2210
CPU MHz:	1800
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	no
Primary Cache:	64KBI + 64KBD on chip per core
Secondary Cache:	1024KB (I+D) on chip per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x512MB, DDR2-667 CL4 ECC Reg
Disk Subsystem:	IDE, 120 GB
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition SP1 (32-bit)
Compiler:	Intel C++ 9.0 build 20050912Z for IA32, Intel Fortran 9.0 build 20050912Z for IA32, Microsoft Visual Studio .NET 7.0.9466 (libraries) PGI Fortran compiler 6.0-5 for Windows XP, PGI C compiler 6.0-5 for Windows XP, ACML Version 2.5.3 (bundled with PGI 6.0-5)
File System:	NTFS
System State:	default

Notes/Tuning Information

```
+FDO:
 icl, ifort  : PASS1=-Qprof_gen  PASS2=-Qprof_use
 pgf90       : PASS1=-Mpfi       PASS2=-Mpfo
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran 90 compiler.
pgcc is the PGI C compiler.
ONESTEP is set to 1 for every compile with the PGI compilers.
Portability:
178.galgel:                -Mfixed
Baseline: C      :  pgcc    -fastsse -Mipa=fast,inline
Baseline: Fortran:  pgf90   -fastsse -Mipa=fast,inline +FDO
Peak tuning:
168.wupwise:        pgf90   -fastsse -Mipa=fast,inline -Mnovect
171.swim:           ifort   -Qipo  -O3  -QaxN -QxW -Qunroll0 +FDO
172.mgrid:          pgf90   -fastsse -Mipa=fast,inline
173.applu:          ifort   -Qipo  -O3 -QaxN -QxW -auto +FDO
177.mesa:           icl     -Qipo -QxW -Qunroll1 -Qansi_alias +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
                        -Qoption,c,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
 178.galgel:         pgf90   -fastsse -Mipa=fast,safe -Munix -lacml
                             RM_SOURCES=lapak.f90
 179.art:            pgcc     basepeak=yes
 183.equake:         icl     -O3 -Qipo -QxW +FDO
 187.facerec:        pgf90   basepeak=1
 188.ammp:           icl     -Oa   -QxW  -Zp4 -Qansi_alias
 189.lucas:          ifort   -Qipo -QxW -Qunroll1
 191.fma3d:          pgf90   -Mipa=fast,inline -fastsse -Mnovect +FDO
 200.sixtrack:       pgf90   -fastsse -Mipa=fast,inline
 301.apsi:           pgf90   -fastsse -Mipa=fast,inline
system can be built using a standard ATX case and a Zippy 700W PSL-6701P power supply
Half memory slots populated on CPU in dual channel configuration
'start /b /wait /affinity' command is used to bind CPU(s) to processes
```