CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

ASUS M2N-LR/SATA, AMD Opteron (TM) 1218

SPECint_rate2000 = 40.8

SPECint_rate_base2000 = 36.3

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	88.4	36.7	2	88.1	36.9
175.vpr	2	117	27.9	2	111	29.3
176.gcc	2	61.7	41.4	2	61.8	41.3
181.mcf	2	306	13.7	2	185	22.5
186.crafty	2	43.2	53.7	2	42.0	55.3
197.parser	2	153	27.3	2	120	34.8
252.eon	2	48.2	62.6	2	41.6	72.4
253.perlbmk	2	103	40.5	2	92.2	45.3
254.gap	2	65.8	38.8	2	65.8	38.8
255.vortex	2	74.0	59.6	2	69.0	63.9
256.bzip2	2	106	32.9	2	106	32.9
300.twolf	2	215	32.3	2	170	40.9

Hardware

CPU:	AMD Opteron (TM) 1218
CPU MHz:	2600
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip per core
Secondary Cache:	1024KB (I+D) on chip per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	2x1024MB, DDR2-800 CL3
Disk Subsystem:	IDE, 120GB
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 9 SP3 (64-bit)
Compiler:	PathScale EKOPath(TM) Compiler Suite, Release 2.3
File System:	Linux/ext3
System State:	Multi-user, run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata  PASS2= -fb_opt fbdata

Baseline optimization flags:
  C programs:       -Ofast +FDO
  C++ programs:     -Ofast +FDO

Portability Flags:
  186.crafty:  -DLINUX_i386
  252.eon:     -DHAS_ERRLIST -DSPEC_CPU2000_LP64
  253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
               -DSPEC_CPU2000_LP64
  254.gap:     -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
               -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
  255.vortex:  -DSPEC_CPU2000_LP64

Peak Tuning:
164.gzip:    -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
175.vpr:     -O3 -ipa -m32 +FDO
176.gcc:     -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
181.mcf:     -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:  -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:  -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:     -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
             -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
             -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
             -fno-math-errno -IPA:plimit=10000 +FDO
255.vortex:  -Ofast -OPT:goto=off -CG:p2align=on
             -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2:   basepeak = true
300.twolf:   -O2 -CG:gcm=off:p2align_freq=100000
             -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
             -WOPT:mem_opnds=on -m32 +FDO

The tested system can be assembled using a standard ATX case and an Antec True 550
watt EPS12V Power Supply.
Half memory slots populated in dual channel configuration.
taskset utility used to bind CPU(s) to processes.
```