CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML150 G3 (3.73 GHz, Intel Xeon processor 5080)

SPECint_rate2000 = 79.7

SPECint_rate_base2000 = 79.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2006 | Hardware Avail: May-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	178	72.9	8	177	73.2
175.vpr	8	263	49.3	8	250	51.9
176.gcc	8	91.7	111	8	91.7	111
181.mcf	8	433	38.6	8	430	38.9
186.crafty	8	146	63.5	8	145	63.9
197.parser	8	209	79.8	8	208	80.4
252.eon	8	95.3	127	8	95.5	126
253.perlbmk	8	179	93.2	8	178	94.0
254.gap	8	134	76.4	8	133	76.6
255.vortex	8	134	132	8	134	131
256.bzip2	8	225	62.0	8	225	62.0
300.twolf	8	267	104	8	266	105

Hardware

CPU:	Intel Xeon processor 5080 (3.73 GHz, 2x2 MB L2, 1066 MHz bus)
CPU MHz:	3730
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1,2 chips
Parallel:	No
Primary Cache:	12 K micro-ops I + 16 KB D on chip per core
Secondary Cache:	2 MB I+D on chip per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8 GB (4x2048 MB PC2-5300F)
Disk Subsystem:	1x36 GB 15 K SAS
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise SP1
Compiler:	Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Base tuning for C programs:   -fast         +FDO  ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO  ONESTEP=yes
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:     -fast               +FDO  ONESTEP=yes
  175.vpr:      -fast               +FDO  ONESTEP=yes
  176.gcc:      basepeak=1
  181.mcf:      -fast               +FDO  ONESTEP=yes shlw32M.lib
  186.crafty:   -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  197.parser:   -fast               +FDO  ONESTEP=yes
  252.eon:      -fast               +FDO
  253.perlbmk:  -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  254.gap:      -fast               +FDO  ONESTEP=yes
  255.vortex:   -fast               +FDO  ONESTEP=yes shlw32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    256.bzip2:    basepeak=1
    300.twolf:    -fast                +FDO              shlw32M.lib
  BIOS Configuration Notes
    Hyper-Threading Technology enabled
    Adjacent Sector Prefetch disabled
```