CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D945GPM motherboard(3.6 GHz, Intel(R) Pentium(TM) D processor)

SPECint_rate2000 = 39.3

SPECint_rate_base2000 = 39.3

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	115	28.2	2	115	28.2
175.vpr	2	123	26.5	2	121	26.8
176.gcc	2	54.6	46.7	2	54.6	46.7
181.mcf	2	110	38.1	2	110	38.1
186.crafty	2	75.5	30.7	2	75.9	30.6
197.parser	2	132	31.6	2	132	31.7
252.eon	2	54.0	55.8	2	54.2	55.6
253.perlbmk	2	84.8	49.3	2	84.9	49.2
254.gap	2	58.6	43.5	2	58.6	43.5
255.vortex	2	63.0	70.0	2	63.0	70.0
256.bzip2	2	117	29.8	2	117	29.8
300.twolf	2	167	41.7	2	167	41.7

Hardware

CPU:	Intel(R) Pentium(TM) D processor 960(3.6 GHz, 800 MHz bus)
CPU MHz:	3600
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-opsI + 16KBD per core, on chip
Secondary Cache:	2MB(I+D) per core, on chip
L3 Cache:	None
Other Cache:	None
Memory:	2 GB (2 1GB Micron DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem:	Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware:	ATI Radeon X1900 XTX PCI express graphics card

Software

Operating System:	Windows XP Professional SP2
Compiler:	Intel C++ Compiler 9.1 for 32-bit applications Build 20060323Z Package ID: W_CC_P_9.1.020 Microsoft Visual Studio 2005(for libraries) SmartHeap Library Version 8.0 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast +FDO shlW32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlW32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon:     -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip:     -fast -Qansi_alias -Oa  +FDO
175.vpr:      -fast -Qansi_alias +FDO
176.gcc:      basepeak=yes
181.mcf:      basepeak=yes
186.crafty:   -fast -Qansi_alias -Oa +FDO
197.parser:   -fast -Qansi_alias  +FDO
252.eon:      -fast +FDO
253.perlbmk:  -fast -Qansi_alias +FDO shlW32M-80.lib
254.gap:      basepeak=yes
255.vortex    basepeak=yes
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
256.bzip2:   -fast -Oa -Qunroll1 +FDO
300.twolf:    -fast -O3 +FDO shlW32M-80.lib
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Product description located as of 07/2006
http://www.intel.com/products/motherboard/dg965wh/index.htm
The system bus runs at 1066 MHz
```