# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## ION

A20 (Intel Xeon processor 5060, 3.2GHz)

SPECint_rate2000 = 66.1

SPECint_rate_base2000 = 66.1

SPEC license #: 2697 | Tested by: ION | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jun-2006




| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|---|---|---|---|---|---|---|
| 164.gzip | 4 | 126 | 51.4 | 4 | 126 | 51.4 |
| 175.vpr | 4 | 142 | 45.8 | 4 | 142 | 45.8 |
| 176.gcc | 4 | 66.9 | 76.3 | 4 | 66.9 | 76.3 |
| 181.mcf | 4 | 154 | 54.2 | 4 | 154 | 54.2 |
| 186.crafty | 4 | 67.5 | 68.7 | 4 | 67.5 | 68.7 |
| 197.parser | 4 | 159 | 52.5 | 4 | 159 | 52.5 |
| 252.eon | 4 | 62.7 | 96.2 | 4 | 62.7 | 96.2 |
| 253.perlbmk | 4 | 95.5 | 87.5 | 4 | 95.5 | 87.5 |
| 254.gap | 4 | 74.5 | 68.5 | 4 | 74.5 | 68.5 |
| 255.vortex | 4 | 79.6 | 111 | 4 | 79.6 | 111 |
| 256.bzip2 | 4 | 141 | 49.4 | 4 | 141 | 49.4 |
| 300.twolf | 4 | 222 | 62.7 | 4 | 222 | 62.7 |

### Hardware

| | |
|---|---|
| CPU: | Intel Xeon Processor 5060 (1066Mhz System Bus) |
| CPU MHz: | 3200 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 2 chips, 2 cores/chip (HyperThreading Technology disabled) |
| CPU(s) orderable: | 1,2 chips |
| Parallel: | No |
| Primary Cache: | 12KB(I) + 16KB(D) on chip, per core |
| Secondary Cache: | 2MB (I+D) on chip, per core |
| L3 Cache: | None |
| Other Cache: | None |
| Memory: | 8 GB (8*1GB PC2-5300 FB-DIMMs) |
| Disk Subsystem: | 1 x 400GB SATA, 7200rpm |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | Red Hat Enterprise Linux ES 4 Update 3 for AMD64/Intel EM64T |
| Compiler: | Intel(R) C++ Compiler for EM64T, V9.1 (Build 20060519) |
| File System: | ext3 |
| System State: | Multi-user |

## Notes/Tuning Information

```
Tested by ION Computer Systems
 BIOS 2.00 Build 54
   HyperThreading Technology Disabled in BIOS
   Enhanced SpeedStep Disabled in BIOS
 kernel 2.6.9-34.0.1.ELsmp
 +FDO: PASS1=-prof_gen  PASS2=-prof_use

 SPEC CINT2000 Baseline optimization flags:
     C programs:     -fast -auto_ilp32 +FDO
   C++ programs:     -fast -ansi_alias +FDO
           +FDO: PASS1=-prof_gen  PASS2=-prof_use

    SPEC CINT2000 Peak optimization flags
      basepeak=yes  set globally

 Portability Flags:
    186.crafty: -DLINUX_i386
       252.eon: -DHAS_ERRLIST
  253.perlbmk: -DSPEC_CPU2000_NEED_BOOL -DSPEC_CPU2000_LINUX_I386
               -DSPEC_CPU2000_LP64
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

```
   254.gap: -DSPEC_CPU2000_LP64 -DSYS_IS_USG
255.vortex: -DSPEC_CPU2000_LP64
```