CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M450 (Intel Core 2 Duo processor E6700)

SPECfp2000 = 2708

SPECfp_base2000 = 2699

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	39.0	4103	38.9	4116
171.swim	3100	116	2673	116	2676
172.mgrid	1800	105	1713	105	1713
173.applu	2100	101	2080	101	2080
177.mesa	1400	55.9	2506	55.7	2515
178.galgel	2900	45.3	6396	45.3	6396
179.art	2600	27.8	9338	27.8	9348
183.equake	1300	38.2	3403	38.2	3401
187.facerec	1900	67.3	2823	67.3	2824
188.ammp	2200	116	1891	111	1978
189.lucas	2000	76.2	2626	76.2	2626
191.fma3d	2100	104	2018	106	1990
200.sixtrack	1100	103	1068	103	1069
301.apsi	2600	144	1809	142	1826



Hardware

CPU:	Intel Core 2 Duo processor E6700
CPU MHz:	2667
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4096KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x 1GB PC2-5300 5-5-5 2Rank SDRAM
Disk Subsystem:	1 x 160GB SATA 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows XP Professional, Service Pack 2
Compiler:	Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20060519Z Package ID: W_CC_P_9.1.025 Intel(R) Fortran Compiler for 32-bit app., Version 9.1, - Build 20060519Z Package ID: W_FC_P_9.1.025 Microsoft Visual Studio .NET 2003 (for libraries) MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)
File System:	FAT32
System State:	Default

Notes/Tuning Information

```
Portability flags:
 178.galgel:  -FI /F32000000

Feedback optimization:
  +FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:
 for C programs:
 -fast +FDO shlW32M.lib
 for Fortran programs:
 -fast +FDO shlW32M.lib

Peak Tuning Flags:
 173.applu:      basepeak=yes
 168.wupwise:  -fast +FDO
 171.swim:     -fast +FDO
 172.mgrid:    -fast +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 173.applu:    basepeak=yes
 177.mesa:     -fast +FDO ONESTEP=yes
 178.galgel:   -fast +FDO
 179.art:      -fast +FDO shlW32M.lib
 183.equake:   -fast +FDO shlW32M.lib
 187.facerec:  -fast +FDO
 188.ammp:     -fast +FDO
 189.lucas:    basepeak=yes
 191.fma3d:    -fast +FDO
 200.sixtrack: -fast +FDO
 301.apsi:     -fast +FDO

Extra Libraries:
 shlW32M.lib = Microquill SmartHeap Library 8
 see www.microquill.com

The system bus runs at 1066 MHz

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```