CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML370 G5 (1.60 GHz, Intel Xeon processor 5110)

SPECint_rate2000 = 71.2

SPECint_rate_base2000 = 71.0

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	144	45.1	4	144	45.1
175.vpr	4	127	51.3	4	121	53.5
176.gcc	4	62.9	81.2	4	62.9	81.2
181.mcf	4	114	73.1	4	114	73.1
186.crafty	4	68.4	67.9	4	68.4	67.8
197.parser	4	145	57.7	4	144	58.1
252.eon	4	62.5	96.6	4	62.3	96.9
253.perlbmk	4	96.0	87.0	4	95.9	87.1
254.gap	4	72.2	70.7	4	73.5	69.4
255.vortex	4	74.2	119	4	74.2	119
256.bzip2	4	135	51.6	4	135	51.6
300.twolf	4	165	84.5	4	165	84.5

Hardware

CPU:	Intel Xeon processor 5110 (1.60 GHz, 4 MB L2 shared, 1066 MHz bus)
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Parallel:	No
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8 GB (8x1024 MB PC2-5300F)
Disk Subsystem:	1x36 GB 10 K SAS
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise SP1
Compiler:	Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast         +FDO  ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO  ONESTEP=yes
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:     -fast               +FDO  ONESTEP=yes
  175.vpr:      -fast               +FDO  ONESTEP=yes
  176.gcc:      basepeak=1
  181.mcf:      -fast               +FDO  ONESTEP=yes shlw32M.lib
  186.crafty:   -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  197.parser:   -fast               +FDO  ONESTEP=yes
  252.eon:      -fast               +FDO
  253.perlbmk:  -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  254.gap:      -fast               +FDO  ONESTEP=yes
  255.vortex:   -fast               +FDO  ONESTEP=yes shlw32M.lib
  256.bzip2:    basepeak=1
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 300.twolf:    -fast                +FDO               shlw32M.lib
BIOS Configuration Notes
  Power Regulator set to Static High Performance Mode
  Adjacent Sector Prefetch Disabled
```