



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS M450 (Intel Core 2 Duo processor E6600)

SPECint_rate2000 = **54.1**
SPECint_rate_base2000 = **53.9**

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	94.8	34.3	2	94.9	34.2
175.vpr	2	84.5	38.4	2	83.3	39.0
176.gcc	2	40.7	62.7	2	40.7	62.7
181.mcf	2	76.8	54.4	2	76.5	54.6
186.crafty	2	45.7	50.8	2	45.2	51.4
197.parser	2	96.5	43.3	2	96.0	43.5
252.eon	2	41.4	72.8	2	41.4	72.8
253.perlbnk	2	61.5	67.9	2	61.5	67.9
254.gap	2	46.7	54.6	2	45.8	55.7
255.vortex	2	47.9	92.0	2	47.9	92.1
256.bzip2	2	90.4	38.5	2	90.5	38.5
300.twolf	2	110	63.3	2	110	63.3

Hardware

CPU: Intel Core 2 Duo processor E6600
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x 1GB PC2-5300 5-5-5 2Rank SDRAM
 Disk Subsystem: 1 x 160GB SATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows XP Professional, Service Pack 2
 Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1,
 - Build 20060519Z Package ID: W_CC_P_9.1.025
 Microsoft Visual Studio .NET 2003 (for libraries)
 MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)
 File System: FAT32
 System State: Default

Notes/Tuning Information

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs:
 -fast +FDO shlW32M.lib
 for C++ program 252.eon:
 -fast -Qcxx_features +FDO

Peak Tuning Flags:

164.gzip: -fast +FDO
 175.vpr: -fast +FDO
 176.gcc: basepeak=yes
 181.mcf: -fast +FDO shlW32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS M450 (Intel Core 2 Duo processor E6600)

SPECint_rate2000 = 54.1
SPECint_rate_base2000 = 53.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

186.crafty: -fast +FDO
197.parser: -fast +FDO
252.eon: -fast -Qcxx_features +FDO
253.perlbnk: -fast +FDO shlw32M.lib
254.gap: -fast +FDO
255.vortex -fast +FDO shlw32M.lib
256.bzip2: -fast +FDO
300.twolf: -fast +FDO shlw32M.lib

Extra Libraries:

shlw32M.lib = Microquill SmartHeap Library 8
see www.microquill.com

The system bus runs at 1066 MHz

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>