CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M450 (Intel Core 2 Duo processor E6600)

SPECint_rate2000 = 54.1

SPECint_rate_base2000 = 53.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	94.8	34.3	2	94.9	34.2
175.vpr	2	84.5	38.4	2	83.3	39.0
176.gcc	2	40.7	62.7	2	40.7	62.7
181.mcf	2	76.8	54.4	2	76.5	54.6
186.crafty	2	45.7	50.8	2	45.2	51.4
197.parser	2	96.5	43.3	2	96.0	43.5
252.eon	2	41.4	72.8	2	41.4	72.8
253.perlbmk	2	61.5	67.9	2	61.5	67.9
254.gap	2	46.7	54.6	2	45.8	55.7
255.vortex	2	47.9	92.0	2	47.9	92.1
256.bzip2	2	90.4	38.5	2	90.5	38.5
300.twolf	2	110	63.3	2	110	63.3

Hardware

CPU:	Intel Core 2 Duo processor E6600
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4096KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x 1GB PC2-5300 5-5-5 2Rank SDRAM
Disk Subsystem:	1 x 160GB SATA 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows XP Professional, Service Pack 2
Compiler:	Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20060519Z Package ID: W_CC_P_9.1.025 Microsoft Visual Studio .NET 2003 (for libraries) MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)
File System:	FAT32
System State:	Default

Notes/Tuning Information

```
Portability flags:
 176.gcc:     -Dalloca=_alloca /F10000000
 186.crafty:  -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Feedback optimization:
  +FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:
 for C programs:
 -fast +FDO shlW32M.lib
 for C++ program 252.eon:
 -fast -Qcxx_features +FDO

Peak Tuning Flags:
 164.gzip:     -fast +FDO
 175.vpr:      -fast +FDO
 176.gcc:      basepeak=yes
 181.mcf:      -fast +FDO shlW32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 186.crafty:    -fast +FDO
 197.parser:    -fast +FDO
 252.eon:       -fast -Qcxx_features +FDO
 253.perlbmk:   -fast +FDO shlW32M.lib
 254.gap:       -fast +FDO
 255.vortex     -fast +FDO shlW32M.lib
 256.bzip2:     -fast +FDO
 300.twolf:     -fast +FDO shlW32M.lib

Extra Libraries:
 shlW32M.lib = Microquill SmartHeap Library 8
 see www.microquill.com

The system bus runs at 1066 MHz

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```