CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel100, Intel Pentium D processor 925, 3.0 GHz

SPECint_rate2000 = 34.8

SPECint_rate_base2000 = 34.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	136	23.9	2	136	23.9
175.vpr	2	136	23.9	2	136	23.9
176.gcc	2	60.5	42.2	2	60.5	42.2
181.mcf	2	111	37.7	2	111	37.7
186.crafty	2	87.8	26.4	2	87.8	26.4
197.parser	2	141	29.7	2	141	29.7
252.eon	2	63.5	47.5	2	63.5	47.5
253.perlbmk	2	97.3	42.9	2	97.3	42.9
254.gap	2	67.7	37.7	2	67.7	37.7
255.vortex	2	73.9	59.6	2	73.9	59.6
256.bzip2	2	132	26.4	2	132	26.4
300.twolf	2	192	36.2	2	192	36.2

Hardware

CPU:	Intel Pentium D processor 925 (3.0 GHz, 2x2MB L2, 800 MHz system bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache:	2048KB(I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x1GB DDRII-RAM PC2-4200E (CAS 4-4-4)
Disk Subsystem:	Western Digital (SATA, 7.2krpm, 160GB)
Other Hardware:	none

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler 9.1 Build 20060323Z (for 32-bit applications), Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries), SmartHeap Library Version 8.0 from http://www.microquill.com
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
GENERAL
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafy:   -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags
   for C programs:   -fast +FDO shlW32M.lib
   for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib

Peak tuning flags
   same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of
the operating system.
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries