CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7110M, 2.60 GHz

SPECfp_rate2000 = 54.2

SPECfp_rate_base2000 = 54.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Feb-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	161	92.3	8	161	92.3
171.swim	8	557	51.7	8	557	51.7
172.mgrid	8	377	44.3	8	377	44.3
173.applu	8	439	44.4	8	439	44.4
177.mesa	8	218	59.5	8	218	59.5
178.galgel	8	320	84.1	8	320	84.1
179.art	8	243	99.5	8	243	99.5
183.equake	8	251	48.0	8	251	48.0
187.facerec	8	280	63.0	8	280	63.0
188.ammp	8	541	37.7	8	541	37.7
189.lucas	8	384	48.3	8	384	48.3
191.fma3d	8	408	47.8	8	408	47.8
200.sixtrack	8	343	29.7	8	343	29.7
301.apsi	8	472	51.1	8	472	51.1

Hardware

CPU:	Intel Xeon processor 7110M (2.60 GHz, 2x1MB L2, 4MB L3, 800 MHz system bus)
CPU MHz:	2600
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1,2,4 chips
Parallel:	No
Primary Cache:	12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache:	1024KB(I+D) on chip, per core
L3 Cache:	4MB on chip, per chip
Other Cache:	N/A
Memory:	16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
Disk Subsystem:	Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
Other Hardware:	none

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 9 with SP3 Kernel 2.6.5-7.244-smp on an x86_64
Compiler:	Intel C++ and Fortran Compiler 9.0 for EM64T Build 20060120 (for 64-bit applications)
File System:	ext3
System State:	Multi-user run level 3

Notes/Tuning Information

```
GENERAL
+FDO implies feedback-directed optimization
PASS1: -prof_gen  PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
   for Fortran and C programs: -fast +FDO

Peak tuning flags
   same as baseline (basepeak=true set globally)
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries