CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECint_rate2000 = 76.6

SPECint_rate_base2000 = 76.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	205	63.5	8	205	63.5
175.vpr	8	257	50.6	8	257	50.6
176.gcc	8	104	97.9	8	104	97.9
181.mcf	8	233	71.6	8	233	71.6
186.crafty	8	170	54.6	8	170	54.6
197.parser	8	225	74.3	8	225	74.3
252.eon	8	111	109	8	111	109
253.perlbmk	8	202	82.6	8	202	82.6
254.gap	8	136	75.3	8	136	75.3
255.vortex	8	150	118	8	150	118
256.bzip2	8	201	69.3	8	201	69.3
300.twolf	8	346	80.4	8	346	80.4

Hardware

CPU:	Intel Xeon processor 7130M (3.20 GHz, 2x1MB L2, 8MB L3, 800 MHz system bus)
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1,2,4 chips
Parallel:	No
Primary Cache:	12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache:	1024KB(I+D) on chip, per core
L3 Cache:	8MB on chip, per chip
Other Cache:	N/A
Memory:	16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
Disk Subsystem:	Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
Other Hardware:	none

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler 9.1 Build 20060323Z (for 32-bit applications), Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries), SmartHeap Library Version 8.0 from http://www.microquill.com
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
GENERAL
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafty:  -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags
   for C programs:   -fast +FDO shlW32M.lib
   for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib

Peak tuning flags
   same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of
the operating system.
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries