# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECint_rate2000 = 76.6

SPECint_rate_base2000 = 76.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006




| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|---|---|---|---|---|---|---|
| 164.gzip | 8 | 205 | 63.5 | 8 | 205 | 63.5 |
| 175.vpr | 8 | 257 | 50.6 | 8 | 257 | 50.6 |
| 176.gcc | 8 | 104 | 97.9 | 8 | 104 | 97.9 |
| 181.mcf | 8 | 233 | 71.6 | 8 | 233 | 71.6 |
| 186.crafty | 8 | 170 | 54.6 | 8 | 170 | 54.6 |
| 197.parser | 8 | 225 | 74.3 | 8 | 225 | 74.3 |
| 252.eon | 8 | 111 | 109 | 8 | 111 | 109 |
| 253.perlbmk | 8 | 202 | 82.6 | 8 | 202 | 82.6 |
| 254.gap | 8 | 136 | 75.3 | 8 | 136 | 75.3 |
| 255.vortex | 8 | 150 | 118 | 8 | 150 | 118 |
| 256.bzip2 | 8 | 201 | 69.3 | 8 | 201 | 69.3 |
| 300.twolf | 8 | 346 | 80.4 | 8 | 346 | 80.4 |

### Hardware

| | |
|---|---|
| CPU: | Intel Xeon processor 7130M (3.20 GHz, 2x1MB L2, 8MB L3, 800 MHz system bus) |
| CPU MHz: | 3200 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled) |
| CPU(s) orderable: | 1,2,4 chips |
| Parallel: | No |
| Primary Cache: | 12k micro-ops(I) + 16KB(D) on chip, per core |
| Secondary Cache: | 1024KB(I+D) on chip, per core |
| L3 Cache: | 8MB on chip, per chip |
| Other Cache: | N/A |
| Memory: | 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3) |
| Disk Subsystem: | Fujitsu MAS3367NC (SCSI, 15krpm, 36GB) |
| Other Hardware: | none |

### Software

| | |
|---|---|
| Operating System: | Windows Server 2003 Enterprise Edition + SP1 (32-bit) |
| Compiler: | Intel C++ Compiler 9.1<br>Build 20060323Z (for 32-bit applications),<br>Microsoft Visual Studio .Net 2003<br>7.1.3088 (for libraries),<br>SmartHeap Library Version 8.0<br>from http://www.microquill.com |
| File System: | NTFS |
| System State: | Default |

## Notes/Tuning Information

```
GENERAL
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafty:  -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags
   for C programs:   -fast +FDO shlW32M.lib
   for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib

Peak tuning flags
   same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of
the operating system.
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

This result was measured on the PRIMERGY TX600 S3. The PRIMERGY TX600 S3 and the PRIMERGY RX600 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries