



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant DL585 G2 (AMD Opteron (TM) 8220SE)

SPECfp\_rate2000 = 174  
SPECfp\_rate\_base2000 = 161

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Sep-2006 Software Avail: Jul-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	62.4	238	8	60.0	248
171.swim	8	184	157	8	180	160
172.mgrid	8	123	135	8	120	140
173.applu	8	116	169	8	103	189
177.mesa	8	64.4	202	8	60.8	214
178.galgel	8	102	265	8	94.3	285
179.art	8	128	189	8	87.4	276
183.quake	8	107	113	8	96.6	125
187.facerec	8	84.7	208	8	83.3	212
188.amp	8	141	144	8	137	149
189.lucas	8	128	145	8	120	155
191.fma3d	8	138	142	8	140	140
200.sixtrack	8	118	86.8	8	112	91.0
301.apsi	8	156	155	8	146	165

### Hardware

CPU: AMD Opteron (TM) 8220SE  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip  
 CPU(s) orderable: 2,4 chips  
 Parallel: No  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 32 GB (16x2 GB PC2-5300P CL5)  
 Disk Subsystem: 1x36.4 GB 10 K SAS  
 Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 3  
 SuSE kernel 2.6.5-7.244-smp  
 Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
 AMD Core Math Library 3.5.0  
 File System: Linux/ext2  
 System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
Portability flags:
  178.galgel: -fixedform
Peak tuning:
  168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
              -IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on
  171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
  172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
              -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2 -WOPT:mem_opnds=on:aggstr=0
  173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
              -LNO:fusion=2:fission=2:full_unroll_size=10000 +FDO
  177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -WOPT:mem_opnds=on +FDO
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL585 G2 (AMD Opteron (TM) 8220SE)

SPECfp\_rate2000 = 174  
SPECfp\_rate\_base2000 = 161

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Jul-2006

## Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex-on RM_SOURCES=lapak.f90 +ACML +FDO
179.art: -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.equake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -LNO:fusion=2 -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
          -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
          -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on -fno-math-errno
          -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes  
Node Interleaving is Disabled

Other Configuration Notes  
Taskset utility used to bind process to CPU(s)