CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 550Q (1650 Mhz, 8 CPU, SLES)

SPECfp_rate2000 = 196

SPECfp_rate_base2000 = 183

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	114	261	16	103	289
171.swim	16	350	164	16	334	172
172.mgrid	16	242	138	16	215	155
173.applu	16	350	111	16	320	122
177.mesa	16	197	132	16	197	132
178.galgel	16	159	339	16	126	427
179.art	16	51.8	932	16	47.7	1011
183.equake	16	82.4	293	16	72.7	332
187.facerec	16	159	222	16	159	222
188.ammp	16	358	114	16	364	112
189.lucas	16	286	130	16	272	136
191.fma3d	16	294	132	16	276	141
200.sixtrack	16	229	89.1	16	223	91.6
301.apsi	16	309	156	16	311	155

Hardware

CPU:	POWER5+
CPU MHz:	1650
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip (SMT on)
CPU(s) orderable:	4,8 core
Parallel:	No
Primary Cache:	64 KB I + 32 KB D on chip per core
Secondary Cache:	1920 KB I+D on chip per chip
L3 Cache:	36 MB I+D off chip per chip
Other Cache:	None
Memory:	32 GB (16x2GB)
Disk Subsystem:	1x73GB SCSI, 15K RPM
Other Hardware:	None

Software

Operating System:	SLES SUSE Linux Enterprise Server 10 (ppc) VERSION = 10 w/2.6.16.21-0.8-ppc64 Linux kernel
Compiler:	IBM XL C/C++ Advanced Edition V8.0.1 for Linux IBM XL Fortran Advanced Edition V10.1.1 for Linux Other software: - IBM Engineering and Scientific Subroutine Library (ESSL) for Linux - Version 4.2.5
File System:	reiserfs
System State:	Multi-User

Notes/Tuning Information

```
+FDO
    Feedback directed optimization enabled by:  PASS1=-qpdf1  PASS2=-qpdf2

FP compilers
   C: invoked as xlc
   Fortran 77 and Fortran 90: invoked as xlf90, except as noted below

FP Portability Flags
  -qfixed used in:        168.wupwise, 171.swim, 172.mgrid, 173.applu,
                          178.galgel, 200.sixtrack, 301.apsi
  -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

FP Base Optimization Flags:
  C:       +FDO -O5
  Fortran: +FDO -O5
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
Floating Point Peak Flags

168.wupwise
    +FDO -O5 -qsave -lmass
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
171.swim
    +FDO -O5
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
172.mgrid
    +FDO -O4 -q64
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
173.applu
    +FDO -O5 -q64
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
177.mesa
    basepeak=1
178.galgel
    Fortran invoked as xlf90_r
    +FDO -O5 -qessl -lessl -lmass
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
179.art
    +FDO -O5
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
183.equake
    +FDO -O5
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
187.facerec
    basepeak=1
188.ammp
    +FDO -O3 -qalign=linuxppc
189.lucas
    +FDO -O3 -qarch=auto -qtune=auto
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
191.fma3d
    +FDO -O5
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
200.sixtrack
    +FDO -O3 -qarch=auto -qtune=auto
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
301.apsi
    Fortran invoked as xlf90_r
    +FDO -O5 -qessl
    -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
    extra_libs = -lessl


System Settings:
-- ulimit stack size set to unlimited


SMT: Acronym for 'Simultaneous Multi-Threading'.  A processor technology that allows
     the simultaneous execution of multiple thread contexts within a single processor
     core. SMT is enabled by default.

Large pages reserved as follows by root user:
    echo 480 > /proc/sys/vm/nr_hugepages
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
System configured with libhugetlbfs library for application access to large pages
Environment variables set as follows:
    export HUGETLB_MORECORE=yes


Each process was bound to a cpu using submit= with the taskset command
   submit = taskset -p -c $SPECUSERNUM $$ >/dev/null ; $command
```