CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec LX211 (Intel Xeon 5110 processor, 1.60GHz)

SPECint_rate2000 = 68.2

SPECint_rate_base2000 = 68.2

SPEC license #: 9001 | Tested by: Itautec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	144	45.0	4	144	45.0
175.vpr	4	131	49.5	4	131	49.5
176.gcc	4	66.1	77.2	4	66.1	77.2
181.mcf	4	139	60.2	4	139	60.2
186.crafty	4	67.5	68.7	4	67.5	68.7
197.parser	4	155	54.0	4	155	54.0
252.eon	4	62.5	96.5	4	62.5	96.5
253.perlbmk	4	101	82.8	4	101	82.8
254.gap	4	77.9	65.5	4	77.9	65.5
255.vortex	4	74.7	118	4	74.7	118
256.bzip2	4	139	50.0	4	139	50.0
300.twolf	4	164	84.8	4	164	84.8

Hardware

CPU:	Intel Xeon 5110 processor (1.60 GHz, 4MB L2 shared, 1066 MHz system bus)
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4096KB(I+D) on chip, per chip, shared
L3 Cache:	N/A
Other Cache:	N/A
Memory:	6x2GB DDR2-RAM PC2-5300F (CAS 5-5-5)ECC
Disk Subsystem:	1 x 120GB Serial ATA 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler 9.1 Build 20060519Z (for 32-bit applications), Microsoft Visual Studio 2005(for libraries), MicroQuill SmartHeap for SMP Library 8.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
PORTABILITY FLAGS
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafy:   -DNT_i386
   252.eon:     -DHAS_ERRLIST
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
GENERAL
   +FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning flags
   for C programs:   -fast -QxP +FDO shlSMPMt.lib
   for C++ programs: -fast -Qcxx_features +FDO
EXTRA LIBRARIES
   MicroQuill SmartHeap for SMP Library 8.0 available from
   http://www.microquill.com/
```