



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3500 (1.6 GHz Xeon E5310, 8MB L2 Cache)

SPECint2000 = --

SPECint_base2000 = 1696

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	141	990			
175.vpr	1400	112	1253			
176.gcc	1100	59.8	1841			
181.mcf	1800	62.3	2889			
186.crafty	1000	67.5	1482			
197.parser	1800	144	1254			
252.eon	1300	62.5	2079			
253.perlbmk	1800	91.4	1970			
254.gap	1100	66.6	1652			
255.vortex	1900	65.0	2925			
256.bzip2	1500	119	1266			
300.twolf	3000	162	1847			

Hardware

CPU: Intel Xeon processor E5310 (1.6 GHz, 1066 MHz bus)
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1, 2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 80GB SATA 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```

This result was measured on an IBM System X 3400. IBM System X 3400 and IBM System X 3500 are electronically equivalent.