



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(1.60GHz, Intel Xeon E5310 processor)

SPECfp_rate2000 = 73.8

SPECfp_rate_base2000 = 74.1

SPEC license #01176 | Tested by: Supermicro | Test date: Nov-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	171	86.8	8	171	87.0
171.swim	8	695	41.4	8	694	41.5
172.mgrid	8	426	39.2	8	427	39.1
173.applu	8	465	41.9	8	465	41.9
177.mesa	8	97.5	133	8	97.5	133
178.galgel	8	119	227	8	119	227
179.art	8	126	192	8	126	192
183.quake	8	223	54.0	8	224	54.0
187.facerec	8	185	95.6	8	188	93.9
188.amp	8	241	84.8	8	245	83.4
189.lucas	8	404	45.9	8	404	46.0
191.fma3d	8	390	49.9	8	390	49.9
200.sixtrack	8	178	57.5	8	181	56.5
301.apsi	8	318	75.9	8	319	75.7

Hardware

CPU: Intel Xeon E5310 processor (1.60 GHz,1066MHz bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1, 2 chip
Parallel: N/A
Primary Cache: 32KBI + 32KBD on chip per core
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 X 2GB DDR2 ECC CL5 667MHz FBDIMM
Disk Subsystem: 1 X Seagate Barracuda 120GB 7200 RPM
Other Hardware: N/A

Software

Operating System: Windows Server 2003 Enterprise Edition 32-bits w/ SP1
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_FC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for 177.mesa: -fast +FDO shlw32M.lib
Base tuning for 179.art: -fast +FDO shlw32M.lib
Base tuning for 183.quake: -fast +FDO shlw32M.lib
Base tuning for 188.amp: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO shlw32M.lib
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(1.60GHz, Intel Xeon E5310 processor)

SPECfp_rate2000 = 73.8

SPECfp_rate_base2000 = 74.1

SPEC license #01176 | Tested by: Supermicro | Test date: Nov-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

```
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlw32M.lib
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi: -fast +FDO
```

Tested systems can be used with SC816S-R700 case,
To ensure system stability, a 500W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of <http://www.supermicro.com/products/motherboard/Xeon1333/5000P/X7DB8.cfm>
The system bus runs at 1066 MHz
shlw32m-80.lib is the V8.0 SmartHeap library renamed to co-exist with older versions