CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX201 (Intel Xeon 5140 processor, 2.33GHz)

SPECfp_rate2000 = 67.7

SPECfp_rate_base2000 = 67.7

SPEC license #: 9001 | Tested by: Itautec | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	75.4	98.5	4	75.4	98.5
171.swim	4	321	44.8	4	321	44.8
172.mgrid	4	205	40.7	4	205	40.7
173.applu	4	240	40.5	4	240	40.5
177.mesa	4	64.9	100	4	64.9	100
178.galgel	4	70.9	190	4	70.9	190
179.art	4	66.4	182	4	66.4	182
183.equake	4	93.7	64.4	4	93.7	64.4
187.facerec	4	108	81.8	4	108	81.8
188.ammp	4	171	59.7	4	171	59.7
189.lucas	4	212	43.8	4	212	43.8
191.fma3d	4	181	53.9	4	181	53.9
200.sixtrack	4	120	42.6	4	120	42.6
301.apsi	4	227	53.1	4	227	53.1

Hardware

CPU:	Intel Xeon 5140 processor (2.33 GHz, 4MB L2 shared, 1333 MHz system bus)
CPU MHz:	2330
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4MB (I+D) on chip, per chip, shared
L3 Cache:	N/A
Other Cache:	N/A
Memory:	14GB (7x2GB DDR2-RAM PC2-5300 FB-DIMM CL5 ECC)
Disk Subsystem:	1 x 120GB Serial ATA 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler 9.1 Build 20060323Z (for 32-bit applications), Intel Fortran Compiler 9.1 Build 20060323Z (for 32-bit applications), Microsoft Visual Studio 2005(for libraries), MicroQuill SmartHeap for SMP Library v.8.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
PORTABILITY FLAGS
   178.galgel:  -FI /F32000000
GENERAL
   +FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Base tuning flags
   for Fortran programs: -fast -Qansi_alias +FDO
   for C programs:       -fast               +FDO shlsmpmt.lib

EXTRA LIBRARIES
  MicroQuill SmartHeap for SMP Library v.8.0
  http://www.microquill.com/

  BIOS settings default.
  The system bus runs at 1333 MHz
  This result was measured with 32-bit binaries using the 32-bit version of the operating system.
```