CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel200 S2, Intel Xeon processor 5130, 2.0 GHz

SPECint_rate2000 = 45.0

SPECint_rate_base2000 = 45.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	115	28.3	2	115	28.3
175.vpr	2	101	32.2	2	101	32.2
176.gcc	2	49.9	51.2	2	49.9	51.2
181.mcf	2	82.4	50.7	2	82.4	50.7
186.crafty	2	55.0	42.2	2	55.0	42.2
197.parser	2	116	36.0	2	116	36.0
252.eon	2	50.4	59.9	2	50.4	59.9
253.perlbmk	2	76.1	54.9	2	76.1	54.9
254.gap	2	56.2	45.4	2	56.2	45.4
255.vortex	2	59.0	74.7	2	59.0	74.7
256.bzip2	2	105	33.0	2	105	33.0
300.twolf	2	132	52.8	2	132	52.8

Hardware

CPU:	Intel Xeon processor 5130 (2.0 GHz, 4MB L2, 1333 MHz system bus)
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2 chips
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4MB(I+D) on chip, per chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem:	Samsung HD160JJ (SATA, 7.2krpm, 160GB)
Other Hardware:	none

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler 9.1 Build 20060323Z (for 32-bit applications), Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries), SmartHeap Library Version 8.0 from http://www.microquill.com
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
GENERAL
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafty:  -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags
   for C programs:   -fast +FDO shlW32M.lib
   for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib

Peak tuning flags
   same as baseline (basepeak=true set globally)

The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of
the operating system.
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
BIOS Configuration:
Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```