CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec LX211 (Intel Xeon 5030 processor)

SPECint_rate2000 = 30.5

SPECint_rate_base2000 = 30.5

SPEC license #: 9001 | Tested by: Itautec | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	244	26.6	4	244	26.6
175.vpr	4	335	19.4	4	335	19.4
176.gcc	4	123	41.6	4	123	41.6
181.mcf	4	463	18.0	4	463	18.0
186.crafty	4	200	23.2	4	200	23.2
197.parser	4	276	30.2	4	276	30.2
252.eon	4	135	44.7	4	135	44.7
253.perlbmk	4	254	32.9	4	254	32.9
254.gap	4	151	33.8	4	151	33.8
255.vortex	4	175	50.4	4	175	50.4
256.bzip2	4	278	25.1	4	278	25.1
300.twolf	4	366	38.1	4	366	38.1

Hardware

CPU:	Intel Xeon 5030 processor (2.66 GHz, 2x2MB L2, 667 MHz system bus)
CPU MHz:	2667
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	2MB (I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	6GB (6x1GB DDR2-RAM PC2-5300 FB-DIMM CL5 ECC)
Disk Subsystem:	1 x 200GB Serial ATA 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler 9.1 Build 20060519Z (for 32-bit applications), Microsoft Visual Studio .NET 7.0.9466 (for libraries), MicroQuill SmartHeap for SMP Library 8.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
PORTABILITY FLAGS
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafty:  -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
GENERAL
   +FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning flags
   for C programs:   -fast +FDO shlSMPMt.lib
   for C++ programs: -fast -Qcxx_features +FDO
EXTRA LIBRARIES
   MicroQuill SmartHeap for SMP Library 8.0 available from
   http://www.microquill.com/
```