CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Bull

NovaScale B260 (Intel Xeon processor 5150, 2.66 GHz)

SPECint2000 = 2696

SPECint_base2000 = 2692

SPEC license #: 20 | Tested by: Bull | Test date: Dec-2006 | Hardware Avail: Dec-2006 | Software Avail: Dec-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	85.0	1646	85.6	1636
175.vpr	1400	71.2	1966	69.9	2004
176.gcc	1100	40.5	2719	40.5	2719
181.mcf	1800	46.6	3866	46.6	3866
186.crafty	1000	41.1	2434	41.1	2434
197.parser	1800	82.3	2187	82.1	2193
252.eon	1300	37.4	3477	37.4	3477
253.perlbmk	1800	55.8	3223	55.8	3223
254.gap	1100	43.0	2557	42.9	2562
255.vortex	1900	42.6	4459	42.6	4459
256.bzip2	1500	74.8	2007	74.8	2007
300.twolf	3000	96.3	3115	96.3	3115



Hardware

CPU:	Intel Xeon Processor 5150 (2.66 GHz, 4MB L2, 1333MHz bus)
CPU MHz:	2660
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip
CPU(s) orderable:	1 to 2 chips
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4096KB(I+D) on chip per chip (shared by 2 cores)
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8GB (2GB DIMMx4, FB-DIMM PC2-5300F ECC CL5)
Disk Subsystem:	1x73GB SAS 10000 rpm
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise Edition (32 bits), Service Pack1
Compiler:	Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20061103Z Package ID: W_CC_C_9.1.033 Microsoft Visual Studio .NET 2003 (for libraries) MicroQuill SmartHeap Library 8.0 (shlW32M.lib)
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
Portability flags:
 176.gcc:     -Dalloca=_alloca /F10000000
 186.crafty:  -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Feedback optimization:
  +FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:
 for C programs:
 -fast +FDO ONESTEP=yes shlW32M.lib
 for C++ program 252.eon:
 -fast -Qcxx_features +FDO ONESTEP=yes

Peak Tuning Flags:
   164.gzip:     -fast +FDO ONESTEP=yes
   175.vpr:      -fast +FDO ONESTEP=yes
   176.gcc:      basepeak=yes
   181.mcf:      basepeak=yes
```

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    186.crafty:   basepeak=yes
    197.parser:   -fast +FDO ONESTEP=yes
    252.eon:      basepeak=yes
    253.perlbmk:  basepeak=yes
    254.gap:      -fast +FDO ONESTEP=yes
    255.vortex:   basepeak=yes
    256.bzip2:    basepeak=yes
    300.twolf:    basepeak=yes


 Other Configuration Notes
   /NUMPROC=1 flag was added to boot.ini to invoke
   uniprocessor environment


For information about Bull please see:
http://www.bull.com
```