CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL360 G5 (2.66 GHz, Intel Xeon processor X5355)

SPECint2000 = 2732

SPECint_base2000 = 2727

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jan-2007 | Hardware Avail: Jan-2007 | Software Avail: Nov-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	84.8	1652	84.9	1649
175.vpr	1400	70.3	1990	69.0	2029
176.gcc	1100	39.7	2773	39.7	2773
181.mcf	1800	42.8	4206	42.6	4226
186.crafty	1000	41.1	2433	41.1	2431
197.parser	1800	82.1	2193	81.8	2200
252.eon	1300	37.5	3467	37.6	3457
253.perlbmk	1800	56.0	3212	55.9	3218
254.gap	1100	42.4	2593	42.4	2593
255.vortex	1900	42.0	4524	42.0	4524
256.bzip2	1500	74.0	2028	74.0	2028
300.twolf	3000	96.1	3121	96.1	3122



Hardware

CPU:	Intel Xeon processor X5355 (2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus)
CPU MHz:	2666
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1,2 chips
Parallel:	No
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip (4 MB shared per 2 cores)
L3 Cache:	N/A
Other Cache:	N/A
Memory:	16 GB (8x2 GB PC2-5300F CL5)
Disk Subsystem:	2x36 GB 10 K SAS
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise x64 Edition SP1
Compiler:	Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20061103Z) Microsoft Visual Studio .NET 2003 (7.1.3088, for libraries) MicroQuill Smartheap Library 8.0
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use

Base tuning for C programs:   -fast         +FDO  ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO  ONESTEP=yes
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:     -fast               +FDO  ONESTEP=yes
  175.vpr:      -fast               +FDO  ONESTEP=yes
  176.gcc:      basepeak=1
  181.mcf:      -fast               +FDO
  186.crafty:   -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  197.parser:   -fast               +FDO  ONESTEP=yes
  252.eon:      -fast               +FDO
  253.perlbmk:  -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  254.gap:      -fast               +FDO  ONESTEP=yes
  255.vortex:   -fast               +FDO  ONESTEP=yes shlw32M.lib
```

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    256.bzip2:    basepeak=1
    300.twolf:    -fast               +FDO              shlw32M.lib
  BIOS Configuration Notes
    Power Regulator set to Static High Performance Mode
    Adjacent Sector Prefetch disabled
  Other Configuration Notes
    The start /b /wait /affinity command is used to bind CPU(s) to processes.
```