CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX221 (Intel Xeon processor E5345, 2.33 GHz)

SPECint_rate2000 = 179

SPECint_rate_base2000 = 179

SPEC license #: 9001 | Tested by: Itautec | Test date: Feb-2007 | Hardware Avail: Feb-2007 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	101	129	8	101	129
175.vpr	8	109	120	8	109	120
176.gcc	8	50.2	203	8	50.2	203
181.mcf	8	151	110	8	151	110
186.crafty	8	46.7	199	8	46.7	199
197.parser	8	105	159	8	105	159
252.eon	8	43.1	280	8	43.1	280
253.perlbmk	8	69.3	241	8	69.3	241
254.gap	8	72.8	140	8	72.8	140
255.vortex	8	57.2	308	8	57.2	308
256.bzip2	8	103	135	8	103	135
300.twolf	8	113	246	8	113	246

Hardware

CPU:	Intel Xeon processor E5345 (2.33 GHz, 2x4MB L2, 1333 MHz system bus)
CPU MHz:	2330
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	8 MB I+D on chip per chip (4 MB shared per 2 cores)
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x2GB DDR2-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem:	1 x 73GB SCSI 10000RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler 9.1 Build 20060519Z (for 32-bit applications), Microsoft Visual Studio .NET 2003 7.1.3088 (for libraries) Microquill SmartHeap Library v.8.0 for SMP
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
GENERAL
Basepeak=yes is used for all programs
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafty:  -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Base tuning flags
   for C programs:   -fast +FDO shlSMPMt.lib
   for C++ programs: -fast -Qcxx_features +FDO  shlSMPMt.lib
EXTRA LIBRARIES
  MicroQuill SmartHeap Library v.8.0 for SMP
  http://www.microquill.com

The Servidor Itautec MX221 and the Servidor Itautec MX201 are electronically equivalent.
```