CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3850 (3.0 GHz Xeon 7120N)

SPECint_rate2000 = --

SPECint_rate_base2000 = 117

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Feb-2007 | Hardware Avail: Oct-2006 | Software Avail: Mar-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	226	115			
175.vpr	16	365	71.2			
176.gcc	16	129	159			
181.mcf	16	608	55.0			
186.crafty	16	179	104			
197.parser	16	297	112			
252.eon	16	119	202			
253.perlbmk	16	229	146			
254.gap	16	204	100			
255.vortex	16	184	191			
256.bzip2	16	276	101			
300.twolf	16	389	143			

Hardware

CPU:	Intel Xeon processor 7120N (3.0 GHz, 667 MHz bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1, 2, 4 chips
Parallel:	No
Primary Cache:	12 K I micro-ops + 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	4 MB on chip per chip
Other Cache:	N/A
Memory:	16 x 2048 MB ECC PC2-3200
Disk Subsystem:	73GB SAS 15K RPM
Other Hardware:	

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler:	Intel C++ Compiler 9.1 for 32-bit applications Build 20060323Z Package ID: W_CC_P_9.1.020 Microsoft Visual Studio 2005(for libraries) SmartHeap Library Version 8.0 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast +FDO shlW32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlW32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon:     -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Bios Settings
   Hardware Prefetch enabled
   Memory Array set to High-Performance Memory Array
```